

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



IPLD6003 Insd M-CBL Conn BLCK

Nsi Industries

Catalog Number	IPLD6003	
Manufacturer	Nsi Industries	
Description	The Polaris IPLD600-3 Multi-Tap Dual-Sided Entry Connector Features 3 Ports Sized For 600 MCM - 6 Awg Wires. The Body Is Made From Aluminum Alloy Wrapped In A Layer Of Plastisol Insulation. Each Dual-Sided Port Is Pre-Loaded With An Oxide Inhibitor, With Removable Access Plugs Over The Hex Screws Used to Tighten The Connections. Installs With A Hex Key and Torque Wrench, Without Any Tape or Additional Supplies. Designed For Use In A Wide Range Of Splicing Applications, Including Installation In Cable Trays	
Weight per unit	1.6 (lbs/each)	
Product Category	Large Terminals & Connectors	
Features		
Material	Aluminum	
Number of Conductors	3	
Poles	1	
Voltage Rating	600 V	
Warranty	1 YEAR	
Wire Size	600 MCM-6 AWG	
Wire Type	Class B & C	
Material, Color, and Finish		
Color	Black	
Finish	Plastisol Insulated	
Dimensions and Weight Size	L=4.550 - W=2.960 - H=3.030	



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	•		
INCC	rin	tions	•
DESI	ли	tions	•
	P		

Description	INSD M-CBL CONN BLCK	
extra long description	NSI IPLD600-3 POLARIS Ins Multi-Tap	
Features	: The Polaris IPLD600-3 3-Port Dual-Sided Connector provides the	
	simplest solution for forming a secure connection between up to	
	three conductors in applications including cable trays, panel	
	boards, ducts, raceways or troughs. Sized for 600 MCM - 6 AWG	
	wires and rated for 600V, this pre-insulated connector comes	
	pre-loaded with an oxide inhibitor and installs faster than	
	traditional uninsulated connector options using just a hex key	
	and torque wrench. The aluminum alloy body is wrapped in high-dielectric s	
Long Description	The Polaris IPLD600-3 Multi-Tap Dual-Sided Entry Connector features 3 ports sized for 600 MCM - 6 AWG wires. The body is	
	made from aluminum alloy wrapped in a layer of plastisol	
	insulation. Each dual-sided port is pre-loaded with an oxide	
	inhibitor, with removable access plugs over the hex screws used	
	to tighten the connections. Installs with a hex key and torque	
	wrench, without any tape or additional supplies. Designed for	
	use in a wide range of splicing applications, including installation in cable trays	
Product Type	Polaris Ins Multi-Tap 600 3 Port Dse	
Special Features	(3) 600 MCM-6 AWG - Dual Rated	
Manufacturer Information		
Brand	Polaris	
GTIN	00662381789501	
Manufacturers Part Number	IPLD600-3	
UPC	662381789501	
Taxonomies, Classifications, and Ca		
Category Description	Comp & Mech Lugs and Butt Splices	
Туре	Double Sided Entry	
Packaging		
Carton	3	
Weight Per each	1.55	
Uses, Certifications, and Standards		
Application	Wire Termination	
environmental conditions	75 C	
standard	UL 486A/B	

75 C

Temperature Rating