

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



IPLD7503 750-250 2S 3 Multi Cable Insul Tap *Nsi Industries*

| Catalog Number | IPLD7503 |
|-----------------------------|--|
| Manufacturer | Nsi Industries |
| Description | The Polaris IPLD750-3 Multi-Tap Dual-Sided Entry Connector Features 3 Ports Sized For 750 - 250 MCM Wires. The Body Is Made From Aluminum Alloy Wrapped In A Layer Of Plastisol Insulation. Each Dual-Sided Port Is Pre-Loaded With An Oxide Inhibitor, With Removable Access Plugs Over The Hex Screws Used to Tighten The Connections. Installs With A Hex Key and Torque Wrench, Without Any Tape or Additional Supplies. Designed For Use In A Wide Range Of Splicing Applications, Including Installation In Cable Trays, |
| Weight per unit | 1.4 (lbs/each) |
| Product Category | Large Terminals & Connectors |
| eatures | |
| Material | Aluminum |
| Number of Conductors | 3 |
| Poles | 1 |
| Voltage Rating | 600 V |
| Warranty | 1 YEAR |
| Wire Size | 750-250 MCM |
| Wire Type | Class B & C |
| laterial, Color, and Finish | |
| Color | Black |
| Finish | Plastisol Insulated |
| imensions and Weight | |
| Size | L=4.950 - W=3.410 - H=3.420 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| | • | | |
|-------|-----|-----|------|
| 11000 | rin | *** | nc |
| Desc | | | 1117 |
| - | | | |

| Description | 750-250 2S 3 MULTI CABLE INSUL TAP |
|-------------------------|---|
| extra long description | NSI IPLD750-3 POLARIS Ins Multi-Tap |
| Features | The Polaris IPLD750-3 3-Port Dual-Sided Connector provides the simplest solution for forming a secure connection between up to three conductors in applications including cable trays, panel boards, ducts, raceways or troughs. Sized for 750 - 250 MCM wires and rated for 600V, this pre-insulated connector comes pre-loaded with an oxide inhibitor and installs faster than traditional uninsulated connector options using just a hex key and torque wrench. The aluminum alloy body is wrapped in high-dielectric stren |
| Long Description | The Polaris IPLD750-3 Multi-Tap Dual-Sided Entry Connector features 3 ports sized for 750 - 250 MCM wires. The body is made from aluminum alloy wrapped in a layer of plastisol insulation. Each dual-sided port is pre-loaded with an oxide inhibitor, with removable access plugs over the hex screws used to tighten the connections. Installs with a hex key and torque wrench, without any tape or additional supplies. Designed for use in a wide range of splicing applications, including installation in cable trays, |
| Product Type | Polaris Ins Multi-Tap 750 3 Port Dse |
| Special Features | (3) 750-250 MCM - Dual Rated |
| anufacturer Information | |
| Rrand | Polaris |

Ma

| Brand | Polaris |
|---------------------------|----------------|
| GTIN | 00662381926012 |
| Manufacturers Part Number | IPLD750-3 |
| UPC | 662381926012 |

Taxonomies, Classifications, and Categories

| Category Description | SPLIT BOLTS |
|----------------------|--------------------|
| Туре | Double Sided Entry |

Packaging

| Carton | 3 |
|-----------------|--------|
| Weight Per each | 1.3999 |

Uses, Certifications, and Standards

| Application | Wire Termination |
|--------------------------|------------------|
| environmental conditions | 90 C |
| standard | UL 486A/B |
| Temperature Rating | 90 C |