

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



IPLD7506 750-250 2S 6 Multi Cable Insul Tap *Nsi Industries*

| Catalog Number | IPLD7506 |
|-----------------------------------|--|
| Manufacturer | Nsi Industries |
| Description | Double Sided Entry Insulated Multi-Tap Connector, 250 MCM Conductor Size, 750 MCM Conductor Size, Insulated, Plastisol Insulation Material, Copper/Aluminum Conductor Material, Black Insulation Color, 6 Conductors, -45 °C Operating Temperature, +90 °C Operating Temperature, 9.23 In Overall Length, 600 V, 2.7999 LB/Ea |
| Weight per unit | 2.8 (lbs/each) |
| Product Category | Large Terminals & Connectors |
| Features | |
| Poles | 1 |
| Voltage Rating | 600 V |
| Warranty | 1 YEAR |
| Wire Size | 750-250 MCM |
| Wire Type | Class B & C |
| Material, Color, and Finish Color | Black |
| Finish | Diactical Inculated |
| Housing Material | |
| Dimensions and Weight | |
| Size | L=9.230 - W=3.410 - H=3.420 |
| | L |
| Descriptions Description | 750-250 2S 6 MULTI CABLE INSUL TAP |
| extra long description | NSI IPLD750-6 POLARIS Ins Multi-Tap |
| Features | The Polaris IPLD750-6 6-Port Dual-Sided Connector provides the |
| - Catares | simplest solution for forming a secure connection between up to |
| | six conductors in applications including cable trays, panel boards, ducts, raceways or troughs. Sized for 750 - 250 MCM wires and rated for 600V, this pre-insulated connector comes pre-loaded with an oxide inhibitor and installs faster than traditional uninsulated connector options using just a hex key and torque wrench. The aluminum alloy body is wrapped in high-dielectric strengt |
| Manufacturer Information | |
| GTIN | 00662381926043 |
| UPC | 662381926043 |



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Taxonomies, Classifications, and | Categories | |
|-----------------------------------|--------------------|--|
| Category Description | SPLIT BOLTS | |
| Туре | Double Sided Entry | |
| Packaging | | |
| Carton | 1 | |
| Weight Per each | 2.7999 | |
| Uses, Certifications, and Standar | ds | |
| Application | Wire Termination | |
| environmental conditions | 90 C | |

UL 486A/B