



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## IPLD7506 750-250 2S 6 Multi Cable Insul Tap

Nsi Industries

|                  |   |
|------------------|---|
| Catalog Number   | IPLD7506  |
| Manufacturer     | Nsi Industries  |
| Description      | Double Sided Entry Insulated Multi-Tap Connector, 250 MCM Conductor Size, 750 MCM Conductor Size, Insulated, Plastisol Insulation Material, Copper/Aluminum Conductor Material, Black Insulation Color, 6 Conductors, -45 °C Operating Temperature, +90 °C Operating Temperature, 9.23 In Overall Length, 600 V, 2.7999 LB/Ea |
| Weight per unit  | 2.8 (lbs/each)  |
| Product Category | Large Terminals & Connectors  |

### Features

|                |             |
|----------------|-------------|
| Material       | Aluminum    |
| Poles          | 1           |
| Voltage Rating | 600 V       |
| Warranty       | 1 YEAR      |
| Wire Size      | 750-250 MCM |
| Wire Type      | Class B & C |

### Material, Color, and Finish

|        |                     |
|--------|---------------------|
| Color  | Black               |
| Finish | Plastisol Insulated |

### Dimensions and Weight

|      |                             |
|------|-----------------------------|
| Size | L=9.230 - W=3.410 - H=3.420 |
|------|-----------------------------|

### Descriptions

|                        |   |
|------------------------|---|
| Description            | 750-250 2S 6 MULTI CABLE INSUL TAP  |
| extra long description | NSI IPLD750-6 POLARIS Ins Multi-Tap   |
| Features               | The Polaris IPLD750-6 6-Port Dual-Sided Connector provides the simplest solution for forming a secure connection between up to six conductors in applications including cable trays, panel boards, ducts, raceways or troughs. Sized for 750 - 250 MCM wires and rated for 600V, this pre-insulated connector comes pre-loaded with an oxide inhibitor and installs faster than traditional uninsulated connector options using just a hex key and torque wrench. The aluminum alloy body is wrapped in high-dielectric strengt |

### Manufacturer Information

|      |                |
|------|----------------|
| GTIN | 00662381926043 |
| UPC  | 662381926043   |



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

|                      |                    |
|----------------------|--------------------|
| Category Description | SPLIT BOLTS        |
| Type                 | Double Sided Entry |

## Packaging

|                 |        |
|-----------------|--------|
| Carton          | 1      |
| Weight Per each | 2.7999 |

## Uses, Certifications, and Standards

|                          |                  |
|--------------------------|------------------|
| Application              | Wire Termination |
| environmental conditions | 90 C             |
| standard                 | UL 486A/B        |
| Temperature Rating       | 90 C             |