



ICA-441WHW – Outdoor Remote Control

Our outdoor remote control gives you access to all the features of your system while outdoors. Designed to be used with wall or overhang mounted speaker model IS-79. Includes surface mounting frame. (One 25 ohm speaker per control.)

ISA-419 – Outdoor Remote Station

Our 5" outdoor cast metal remote speaker provides quality sound in any weather. Use on patio, deck or at the pool to stay in touch with those inside or to listen to music.

ISA-449WH – Outdoor Remote Station

Enhance the ambiance of the outdoors with the NuTone® 5" outdoor remote speaker. Ideal for use on a patio or deck. Includes surface mounting frame.



ICA-441WHW



ISA-449WH



ISA-419

IMA-4406 System Components

Order Rough-in PLUS finish kit to make a complete unit.

Finish Kit Model No.	Finish	Width	Height	In-Wall Depth	Projects	Rough-In Model No.
'Master' Stations						
IMA-4406BL IMA-4406L IMA-4406WH	Black Biscuit Bright White	17-3/4"	10-1/8"	3-1/2"	1-7/8"	IR-105
IAA-440 (Expansion Kit – adds an additional 6 stations)						
Indoor Remote Stations/Control						
ICA-441WH	Bright White	7"	4"	1-1/16"	7/8"	IR-91
ISA-445BL ISA-445D ISA-445L ISA-445WH	Black Sable Brown Biscuit Bright White	6-5/16"	8-1/4"	1-7/16"	7/8"	IR-50
ISA-448BL ISA-448L ISA-448WH	Black Biscuit Bright White	10"	11-1/4"	2-3/4"	7/8"	IR-80
Outdoor Remote Stations/Control						
ICA-441WHW	Bright White	7"	4"	Surface Mount	2-1/2"	–
ISA-419AB ISA-419PB ISA-419WH	Antique Brass Polished Brass Bright White	6-1/4"	8-3/16"	1-7/8"	7/16"	IR-50* or IR-55*
ISA-449WH	Bright White	6-11/16"	8-9/16"	Surface Mount	3-1/2"	–

Intercom Options:

See p. 31 for chime modules and audio wall plate, p. 24-25 for music speaker options, p. 26-29 for door and intercom speakers and p. 39 for update and surface frames.

NuTone® products should not be installed on outside walls unless they are specifically designed for outside use.

NuTone® Intercom Wire is an integral part of all NuTone® Radio Intercom Systems; such wire has been designed to enable full system performance and to minimize outside interference, dimmer noise, radio frequency interference and other reception problems. If wire other than NuTone® specified wire is used in the installation of a NuTone® Radio Intercom, the Warranty shall not be applicable to any defect or problem relating to the use of non-NuTone® specified wire.

Installation Wire: NuTone® 3-twisted-pair/6-wire cable: 200 ft. (IW-6-200), 1000 ft. (IW-6-1000), NuTone® twisted-pair 22/2 cable: 100 ft. (IW-2-100), 500 ft. (IW-2-500), twisted-pair 18/2: (S-143-500). For installations where UL listed wire is specified, add 'UL' suffix to model number when ordering.

IMA-4406 'Master' station powered by (2) 18 volt, 72 VA transformers NuTone® model 801T supplied with the IR-105 rough-in.

*ISA-419AB, ISA-419PB and ISA-419WH use model IR-50 rough-in for non-masonry installation or model IR-55 rough-in when mounting to stucco or brick.



ICA-441WHW – Outdoor Remote Control

Our outdoor remote control gives you access to all the features of your system while outdoors. Designed to be used with wall or overhang mounted speaker model IS-79. Includes surface mounting frame. (One 25 ohm speaker per control.)

ISA-419 – Outdoor Remote Station

Our 5" outdoor cast metal remote speaker provides quality sound in any weather. Use on patio, deck or at the pool to stay in touch with those inside or to listen to music.

ISA-449WH – Outdoor Remote Station

Enhance the ambiance of the outdoors with the NuTone® 5" outdoor remote speaker. Ideal for use on a patio or deck. Includes surface mounting frame.



ICA-441WHW



ISA-449WH



ISA-419

IMA-4406 System Components

Order Rough-in PLUS finish kit to make a complete unit.

Finish Kit Model No.	Finish	Width	Height	In-Wall Depth	Projects	Rough-In Model No.
'Master' Stations						
IMA-4406BL IMA-4406L IMA-4406WH	Black Biscuit Bright White	17-3/4"	10-1/8"	3-1/2"	1-7/8"	IR-105
IAA-440 (Expansion Kit – adds an additional 6 stations)						
Indoor Remote Stations/Control						
ICA-441WH	Bright White	7"	4"	1-1/16"	7/8"	IR-91
ISA-445BL ISA-445D ISA-445L ISA-445WH	Black Sable Brown Biscuit Bright White	6-5/16"	8-1/4"	1-7/16"	7/8"	IR-50
ISA-448BL ISA-448L ISA-448WH	Black Biscuit Bright White	10"	11-1/4"	2-3/4"	7/8"	IR-80
Outdoor Remote Stations/Control						
ICA-441WHW	Bright White	7"	4"	Surface Mount	2-1/2"	–
ISA-419AB ISA-419PB ISA-419WH	Antique Brass Polished Brass Bright White	6-1/4"	8-3/16"	1-7/8"	7/16"	IR-50* or IR-55*
ISA-449WH	Bright White	6-11/16"	8-9/16"	Surface Mount	3-1/2"	–

Intercom Options:

See p. 31 for chime modules and audio wall plate, p. 24-25 for music speaker options, p. 26-29 for door and intercom speakers and p. 39 for update and surface frames.

NuTone® products should not be installed on outside walls unless they are specifically designed for outside use.

NuTone® Intercom Wire is an integral part of all NuTone® Radio Intercom Systems; such wire has been designed to enable full system performance and to minimize outside interference, dimmer noise, radio frequency interference and other reception problems. If wire other than NuTone® specified wire is used in the installation of a NuTone® Radio Intercom, the Warranty shall not be applicable to any defect or problem relating to the use of non-NuTone® specified wire.

Installation Wire: NuTone® 3-twisted-pair/6-wire cable: 200 ft. (IW-6-200), 1000 ft. (IW-6-1000), NuTone® twisted-pair 22/2 cable: 100 ft. (IW-2-100), 500 ft. (IW-2-500), twisted-pair 18/2: (S-143-500). For installations where UL listed wire is specified, add 'UL' suffix to model number when ordering.

IMA-4406 'Master' station powered by (2) 18 volt, 72 VA transformers NuTone® model 801T supplied with the IR-105 rough-in.

*ISA-419AB, ISA-419PB and ISA-419WH use model IR-50 rough-in for non-masonry installation or model IR-55 rough-in when mounting to stucco or brick.