

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

ITCSN1100 Heat Shrink Heavy-Wall Cable Sleeve Itcsn-1100 Minnesota Mining (3M)

Catalog Number	ITCSN1100
Manufacturer	Minnesota Mining (3M)
Description	3M™ Heat Shrink Cable Sleeve Itcsn Is A Heavy Wall Sleeve That
	Provides Abrasion, Corrosion and Chemical Resistance. This
	Sleeve Has A 3:1 Shrink Ratio to Offer Electrical Insulation For 1
	KV Rated Applications. It Features A Cross Linked Polyolefin
	Construction That Provides Moisture Seal Protection.
Weight per unit	0.1669 (lbs/each)
Product Category	Splicing & Terminating Kits
Descriptions	
Description	HEAT SHRINK HEAVY-WALL CABLE SLEEVE ITCSN-1100
extra long description	3M 7010305769 3M™ Heat Shrink Heavy
Features Long Description	3M™ Heat Shrink Cable Sleeve ITCSN is a split resistant sleeve
	with a factory applied adhesive/sealant that offers reliable
	performance for electrical splices, connections and terminations
	It is perfect for insulating secondary splices, direct buried,
	submersible or dig in repairs, as well as physical protection of
	high voltage, air insulated connectors or lugs. It withstands
	temperatures of 67 to 230 degrees F (55 to 110 degrees C). UL
	Listed, CSA Certified and RoHS 2011/65/EU Compliant.
	3M™ Heat Shrink Cable Sleeve ITCSN is a heavy wall sleeve that provides abrasion, corrosion and chemical resistance. This sleeve
	has a 3:1 shrink ratio to offer electrical insulation for 1 kV rated
	applications. It features a cross linked polyolefin construction
	that provides moisture seal protection.
Product Type	3M™ Heat Shrink Heavy-Wall Cable Sleeves Itcsn
Manufacturer Information	
Brand	3M
GTIN	00051128600795
Manufacturers Part Number	7010305769
UPC	051128600795
Taxonomies, Classifications, and (Categories
Category Description	HEAT/COLD SHRINK
Туре	Heavy Wall
Packaging	
Carton	12

0.1669

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards		
standard	UL, CSA	