


## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





## **ITG30 3/0-#4 Polaris Insul-Tap Connector For Dlo Cable** *Nsi Industries*

Catalog Number	ITG30
Manufacturer	Nsi Industries
Description	Multi-Tap Connector, #4 Awg Conductor Size, 3/0 Awg Conductor Size, Insulated, Plastisol Insulation Material, Copper Conductor Material, Gray Insulation Color, 2 Conductors, -45 °C Operating Temperature, +90 °C Operating Temperature, 1.85 In Overall Length, 600 V Ac, 0.19 LB/Ea
Weight per unit	· · · · · · · · · · · · · · · · · · ·
Product Category	Large Terminals & Connectors
Features	
Number of Conductors	2
Poles	1
Voltage Rating	600 V
Warranty	
Wire Size	(Class B,C,D) 3/0-4 AWG - (Class K,M,I) 2/0-2 AWG
Wire Type	B,C,D,K,M,I
Material, Color, and Finish	
Color	•
Finish	Plastisol Insulated
Housing Material	Aluminum
<b>Dimensions and Weight</b>	
Size	L=1.850 - W=1.600 - H=1.810
Descriptions	
Description	3/0-#4 POLARIS INSUL-TAP CONNECTOR FOR DLO CABLE
extra long description	NSI ITG-3/0 POLARIS Grey Multi-Tap
Features	The Polaris ITG-3/0 2-Port Single-Side Connector provides the
	simplest solution for forming a secure connection between two
	fine-stranded wire conductors in applications including cable
	trays, troughs, wire-ways, raceways, ducts and motor junction
	boxes. Sized for 3/0 - 4 AWG wires and rated for 600V, this
	pre-insulated connector comes pre-loaded with an oxide inhibitor and installs faster than traditional uninsulated
	connector options using just a hex key and torque wrench. The
	aluminum alloy body is wrap
Manufacturer Information	
GTIN	00662381951533
UPC	662381951533



standard

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and	Categories	
Category Description	SPLIT BOLTS	
Туре	Multi Cable	
Packaging		
Carton	3	
Package	6	
Weight Per each	0.19	
Uses, Certifications, and Standard	ls	
	Wire Termination	
environmental conditions	90 C	

UL 486A/B