



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



K0509 1/2 90D Liqтите Conn *Hubbell--Killark*

Catalog Number	K0509
Manufacturer	Hubbell--Killark
Description	1/2" 90° Liquidtight Connector Non-Insulated
Weight per unit	0.2600 (lbs/each)
Product Category	Liquid Tight Fittings

Features

insulation	False
Insulation Type	Non-Insulated
Material	Steel

Material, Color, and Finish

Color	Gray
Finish	Zinc Plated

Dimensions and Weight

Length	1-3/4
Size	1-3/4" L x 1-1/8" W x 1-1/2" H
Width	1-1/8

Descriptions

Description	1/2 90D LIQTITE CONN
extra long description	KLRK K0509 1/2" 90° LT CON STEEL NO
Long Description	1/2" 90° Liquidtight Connector Non-Insulated
Product Type	1/2" 90° LT Con Steel Non-Insulated
Special Features	Liquidtight fittings are used with metallic and non-metallic conduit to seal out water, oil, and dust in applications food processors, beverage & chemical plants, plastics fabricators, machine shops, etc.

Manufacturer Information

Brand	KILLARK
GTIN	00783936997988
Manufacturers Part Number	K0509
series	K Series
sub brand	LIQUIDTIGHT
UPC	783936997988

Taxonomies, Classifications, and Categories

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Type	90 Degree Liquidtight Non-Insulated Connector



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton	1
Package	25
Weight Per each	0.26

Uses, Certifications, and Standards

Application	Use with metallic and non-metallic conduit to seal out water, oil, and dust in applications for food processors, beverage and chemical plants, plastics fabricators, machine shops, etc. Liquidtight connectors are also suitable for use in hazardous location
environmental conditions	Hazardous locations
standard	UL, CSA