LC4500 Series
Thermal-Type Photo Controls

- Locking-Type Mounting
- Controls street lighting and other applications requiring twist and lock plug connection
- Integral high impact thermoplastic housing
- Complies with ANSI C136.10 Standard
- Dual temperature compensating bi-metal and composite resistor
- Dusk-to-Dawn lighting control
- Delay feature prevents unwanted OFF switching
- 2-year warranty

	Model #	Watts Tungsten	VA Ballast	Voltage 50/60 Hz	Agency/Listing
E.	**LC4521C**	1800	1000	120	UL, CSA
	LC4523	3100-4155	1700-2300	208-277	UL, CSA
	LC4527	5205	2880	347	CSA
	LC4535	7200	4000	480	UL, CSA
	LC4536C	1800-4155	1000-2290	120-277	UL, CSA
	LC4521LA*	1800	1000	120	UL, CSA
	LC4523LA*	3100-4155	1700-2300	208-277	UL, CSA
	LC4535LA*	7200	4000	480	UL, CSA
	LC4536LAC*	1800-4155	1000-2290	120-277	UL, CSA

**Models equipped with a 2400 volt open type spark gap arrester.*

Rating:
Tungsten Amps: 15
Ballast Amps: 8.3
Power Consumption: Averages under 1 W
Activation: .5 FC minimum ON, 15 FC maximum OFF
Color: Translucent with color-coded band for voltage identification
Dimensions: 2 ¾" (7.0 cm) H x 3" (7.6 cm) ø

E.

Accessories for Photo Controls

F.

G.

H.

J.

	Model #	Description	Rating	Agency Listing
F.	**K122**	Outdoor Locking-Type Receptacle with Pole Bracket	15 A Max, 480 Volt Max.	UL
G.	**K121**	Locking-Type Receptacle with 9" Leads	15 A Max, 480 Volt Max.	cULus
	K121-30	Locking-Type Receptacle with 30" Leads	15 A Max, 480 Volt Max.	CSA
H.	**K4500**	Shorting Cap	15 A Max, 480 Volt Max.	UL, CSA
J.	**K42-SW-A**	Swivel Assembly for K4100, K4200 Series	–	–

Rating:
Pole Bracket Adapters: For use with all locking-type photo controls
Shorting Cap K4500: 105-480 Volts; replaces locking-type photo control to complete circuit
Dimensions: 2 ¾" (7.0 cm) H x 3" (7.6 cm) ø

LC4500 Series
Thermal-Type Photo Controls

- Locking-Type Mounting
- Controls street lighting and other applications requiring twist and lock plug connection
- Integral high impact thermoplastic housing
- Complies with ANSI C136.10 Standard
- Dual temperature compensating bi-metal and composite resistor
- Dusk-to-Dawn lighting control
- Delay feature prevents unwanted OFF switching
- 2-year warranty

	Model #	Watts Tungsten	VA Ballast	Voltage 50/60 Hz	Agency/Listing
E.	**LC4521C**	1800	1000	120	UL, CSA
	LC4523	3100-4155	1700-2300	208-277	UL, CSA
	LC4527	5205	2880	347	CSA
	LC4535	7200	4000	480	UL, CSA
	LC4536C	1800-4155	1000-2290	120-277	UL, CSA
	LC4521LA*	1800	1000	120	UL, CSA
	LC4523LA*	3100-4155	1700-2300	208-277	UL, CSA
	LC4535LA*	7200	4000	480	UL, CSA
	LC4536LAC*	1800-4155	1000-2290	120-277	UL, CSA

**Models equipped with a 2400 volt open type spark gap arrester.*

Rating:
Tungsten Amps: 15
Ballast Amps: 8.3
Power Consumption: Averages under 1 W
Activation: .5 FC minimum ON, 15 FC maximum OFF
Color: Translucent with color-coded band for voltage identification
Dimensions: 2 ¾" (7.0 cm) H x 3" (7.6 cm) ø

E.

Accessories for Photo Controls

F.

G.

H.

J.

	Model #	Description	Rating	Agency Listing
F.	**K122**	Outdoor Locking-Type Receptacle with Pole Bracket	15 A Max, 480 Volt Max.	UL
G.	**K121**	Locking-Type Receptacle with 9" Leads	15 A Max, 480 Volt Max.	cULus
	K121-30	Locking-Type Receptacle with 30" Leads	15 A Max, 480 Volt Max.	CSA
H.	**K4500**	Shorting Cap	15 A Max, 480 Volt Max.	UL, CSA
J.	**K42-SW-A**	Swivel Assembly for K4100, K4200 Series	–	–

Rating:
Pole Bracket Adapters: For use with all locking-type photo controls
Shorting Cap K4500: 105-480 Volts; replaces locking-type photo control to complete circuit
Dimensions: 2 ¾" (7.0 cm) H x 3" (7.6 cm) ø