



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## **K150 1 1/2 STR Liqtite Conn** *Hubbell--Killark*

Catalog Number	K150
Manufacturer	Hubbell--Killark
Description	1 1/2" Straight Liquidtight Connector Non-Insulated
Weight per unit	0.7500 (lbs/each)
Product Category	Liquid Tight Fittings

### **Features**

insulation	False
Insulation Type	Non-Insulated
Material	Steel

### **Material, Color, and Finish**

Color	Gray
Finish	Zinc Plated

### **Dimensions and Weight**

Length	2-3/8
Size	2-3/8" L x 2-7/32" W x 2-7/32" H
Width	2-7/32

### **Descriptions**

Description	1 1/2 STR LIQTITE CONN
extra long description	KLRK K150 1 1/2" STR LT CONNECTOR N
Long Description	1 1/2" Straight Liquidtight Connector Non-Insulated
Product Type	1 1/2" STR LT Connector Non-Insulated
Special Features	Liquidtight fittings are used with metallic and non-metallic conduit to seal out water, oil, and dust in applications food processors, beverage & chemical plants, plastics fabricators, machine shops, etc.

### **Manufacturer Information**

Brand	KILLARK
GTIN	00783936991276
Manufacturers Part Number	K150
series	K Series
sub brand	LIQUIDTIGHT
UPC	783936991276

### **Taxonomies, Classifications, and Categories**

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Type	Straight Liquidtight Non-Insulated Connector



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Packaging

Carton	1
Package	1280
Weight Per each	0.75

## Uses, Certifications, and Standards

Application	Use with metallic and non-metallic conduit to seal out water, oil, and dust in applications for food processors, beverage and chemical plants, plastics fabricators, machine shops, etc. Liquidtight connectors are also suitable for use in hazardous location
environmental conditions	Hazardous locations
standard	UL, CSA