

K2C20B1, SERVIT POST Mechanical Connector, 2 Cables to Flat

By Burndy Catalog # K2C20B1

Mechanical Grounding Connector, 2 Cables to Flat, 10 - 5 AWG (Str) / 10 - 4 AWG (Sol), 5/16" Stud.



Application

For Used To Ground One Or Two Copper Cables To Steel Structures, Fence Posts, Transformers, Tap One Or Two Cables From Bus Bar And Direct Burial

General

EU RoHS Indicator Yes

Material Bronze Alloy, Leaded

Plated N

Plating Type Unplated
Stud Installation Torque inch 180 LBS/in

pounds

Sub BrandSERVIT POSTTrade NameSERVIT POST™TypeKC and K2C SeriesUPC781810257050UPC 12 Digit7818102570500

Dimensions

Dimension - B Length fraction 27/32 in Dimension - B Length inch 0.85 in Dimension - Body Width inch 0.50 in Dimension - Bolt Size fraction 5/16 Dimension - D inch 1.00 in Dimension - Height fraction 7/8 Dimension - Height inch 0.86 in Dimension - L Length Overall 48.8 mm

mm

Dimension - Length Overall 1.92 in

inch

Dimension - Nut Width inch

Dimension - P inch

Dimension - Threads per inch

18

Conductor Related

Conductor - Copper Solid Size 10 AWG;9 AWG;8 AWG;7

AWG;6 AWG;5 AWG;4 AWG

Conductor - Copper Solid Size 10 AWG-4 AWG

Range

Conductor - Copper Str Size 10 AWG;9 AWG;8 AWG;7

AWG;6 AWG;5 AWG

10 AWG-5 AWG

Conductor - Copper Str Size

Range

Physical Attribute - Number of 2 Conductors Accommodated

Tota

Certifications and Compliance

Certification - CSA Approved No
Certification - ETL No
Certification - UL Listed Direct Yes

Burial

Certification - UL Recognized No
Certification - cULus No
Industry Standard(s) UL467
Standards - Industry UL467

Standards Met

Standards - RoHS Compliance EX

Status

UL Listed Yes

Logistics

Carton Quantity 50 Minimum Pack Quantity 1

Pallet Quantity 19800

Product Assets

Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Sales Drawings - SD..055917

