

# K2C22, SERVIT POST Mechanical Connector, 2 Cables to Flat

By Burndy Catalog # K2C22

Mechanical Grounding Connector, 2 Cables to Flat, 10 - 3 AWG (Str) / 10 - 2 AWG (Sol), 3/8" Stud.



## **Application**

For Used To Ground One Or Two Copper Cables To Steel Structures, Fence Posts, Transformers, Tap One Or Two Cables From Bus Bar And Direct Burial

#### General

**EU RoHS Indicator** 

Material Bronze Alloy, Leaded

Plated

Unplated Plating Type 280 LBS/in

Stud Installation Torque inch

pounds

SERVIT POST Sub Brand Trade Name SERVIT POST™ Туре KC and K2C Series UPC 781810257104 UPC 12 Digit 7818102571044

#### **Dimensions**

Dimension - B Length fraction 15/32 in Dimension - B Length inch 0.46 in Dimension - Body Width inch 0.62 in Dimension - Bolt Size fraction 3/8 Dimension - D inch 0.62 inDimension - Height fraction 1.25 in Dimension - Height inch Dimension - L Length Overall 41.1 mm Dimension - Length Overall 1.62 in 0.75 in Dimension - Nut Width inch 0.26 in Dimension - Pinch Dimension - Threads per inch Dimension - Width inch 32 mm

### **Conductor Related**

Conductor - Copper Solid Size 10 AWG;9 AWG;8 AWG;7

AWG;6 AWG;5 AWG;4 AWG;3

AWG:2 AWG

3 AWG - 10 AWG

Conductor - Copper Solid Size 2 AWG - 10 AWG

Range

10 AWG;9 AWG;8 AWG;7 Conductor - Copper Str Size

AWG;6 AWG;5 AWG;4 AWG;3

AWG

Conductor - Copper Str Size

Range

Physical Attribute - Number of 2 Conductors Accommodated

Total

### **Certifications and Compliance**

Certification - CSA Approved Nο Certification - ETL No Certification - UL Listed Direct Yes

Burial

Certification - UL Recognized Nο Certification - cULus Industry Standard(s) **UL467** Standards - Industry **UL467** 

Standards Met

Standards - RoHS Compliance

Status

**UL** Listed Yes

#### Logistics

Carton Quantity 50 Minimum Pack Quantity Pallet Quantity 14850

#### **Product Assets**

3D Models - K2C22 MODEL-PDF 3D Models - K2C22 MODEL-STEP 3D Models - K2C22\_MODEL-IGES Customer Notices - Prop 65 Notice Sales Drawings - SD..055917

