

K2C23, SERVIT POST Mechanical Connector, 2 Cables to Flat

By Burndy Catalog # K2C23

Mechanical Grounding Connector, Cable to Flat, 8-2 AWG (Str) / 10-1 AWG (Sol), 3/8" Stud, cross base flat ::62.



Application

For Direct Burial Applications And Used To Ground One Or Two Cables To Steel Structures, Fence Posts, Transformers, Also Used To Tap One Or Two Cables From Bus Bar

General

EU RoHS Indicator Yes

Material Bronze Alloy, Leaded

Plated

Plating Type Unplated
Stud Installation Torque inch 280 LBS/in

pounds

Sub BrandSERVIT POSTTrade NameSERVIT POST™TypeKC and K2C SeriesUPC781810257203UPC 12 Digit7818102572033

Dimensions

Dimension - B Length fraction 15/32 in Dimension - B Length inch 0.46 in Dimension - Body Width inch 0.62 in Dimension - Bolt Size fraction 3/8 Dimension - D inch 0.62 inDimension - Height fraction 1.34 in Dimension - Height inch Dimension - L Length Overall 56 mm Dimension - Length Overall 2.19 in Dimension - Nut Width inch 0.81 in 0.32 in Dimension - Pinch Dimension - Threads per inch Dimension - Width inch 34 mm

Conductor Related

Conductor - Copper Solid Size 10 AWG;9 AWG;8 AWG;7

AWG;6 AWG;5 AWG;4 AWG;3

AWG;2 AWG;1 AWG

2 AWG - 8 AWG

Conductor - Copper Solid Size 1 AWG - 10 AWG

Range

Conductor - Copper Str Size 8 AWG;7 AWG;6 AWG;5

AWG;4 AWG;3 AWG;2 AWG

Conductor - Copper Str Size

Range

Physical Attribute - Number of 2 Conductors Accommodated

Tota

Certifications and Compliance

Certification - CSA Approved No Certification - ETL No Certification - UL Listed Direct Yes

Burial

Certification - UL Recognized No
Certification - cULus No
Industry Standard(s) UL467
Standards - Industry UL467

Standards Met

Standards - RoHS Compliance EX

Status

UL Listed Yes

Logistics

Carton Quantity 50
Minimum Pack Quantity 1
Pallet Quantity 14850

Product Assets

3D Models - K2C23_MODEL-STEP 3D Models - K2C23_MODEL-PDF 3D Models - K2C23_MODEL-IGES Customer Notices - Prop 65 Notice Sales Drawings - SD..055917

