

K2C26B1, SERVIT POST Mechanical Connector, 2 Cables to Flat

By Burndy Catalog # K2C26B1

Mechanical Grounding Connector, Cable to Flat, 2-2/0 AWG (Str) / 2-3/0 AWG (Sol), 1/2" Stud,1-3/8 H.



Application

For Direct Burial Applications And Used To Ground One Or Two Cables To Steel Structures, Fence Posts, Transformers, Also Used To Tap One Or Two Cables From Bus Bar

General

EU RoHS Indicator Yes

Material Bronze Alloy, Leaded

Plated N

Plating Type Unplated
Stud Installation Torque inch 480 LBS/in

pounds

Sub BrandSERVIT POSTTrade NameSERVIT POST™TypeKC and K2C SeriesUPC781810257456UPC 12 Digit7818102574566

Dimensions

Dimension - B Length fraction 1-1/16 in Dimension - B Length inch 1.04 in Dimension - Body Width inch 0.88 in Dimension - Bolt Size fraction 1/2 Dimension - D inch 1.25 in Dimension - Height fraction 1-3/8 Dimension - Height inch 1.38 in 78 mm Dimension - L Length Overall Dimension - Length Overall 3.09 in Dimension - Nut Width inch 1.04 in 0.44 in Dimension - Pinch Dimension - Threads per inch

Conductor Related

Conductor - Copper Solid Size 2 AWG;1/0 AWG;2/0

AWG;3/0 AWG

Conductor - Copper Solid Size 2 AWG-3/0 AWG

Range

Conductor - Copper Str Size 2 AWG;1 AWG;1/0 ;2/0 AWG

Conductor - Copper Str Size 2 AWG-2/0 AWG

Range

Physical Attribute - Number of 2 Conductors Accommodated

Total

Certifications and Compliance

Certification - CSA Approved No Certification - ETL No Certification - UL Listed Direct Yes

Burial

Certification - UL Recognized No
Certification - cULus No
Industry Standard(s) UL467
Standards - Industry UL467

Standards Met

Standards - RoHS Compliance EX

Status

UL Listed Yes

Logistics

Carton Quantity 25
Minimum Pack Quantity 1
Pallet Quantity 5800

Product Assets

3D Models - K2C26B1_MODEL-STEP 3D Models - K2C26B1_MODEL-IGES 3D Models - K2C26B1_MODEL-PDF Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Sales Drawings - SD..055917

