

# K2C28B1, SERVIT POST Mechanical Connector, 2 Cables to Flat

By Burndy Catalog # K2C28B1

Mechanical Grounding Connector, Cable to Flat, 1-4/0 AWG, 5/8" Stud.



## **Application**

For Used To Ground One Or Two Copper Cables To Steel Structures, Fence Posts, Transformers, Tap One Or Two Cables From Bus Bar And Direct Burial

### General

**EU RoHS Indicator** 

Material Copper Alloy

Plated

Unplated Plating Type Stud Installation Torque inch 660 LBS/in

pounds

SERVIT POST Sub Brand Trade Name SERVIT POST™ Туре KC and K2C Series UPC 781810257555 UPC 12 Digit 7818102575555

#### **Dimensions**

Dimension - B Length fraction 1-1/4 in Dimension - B Length inch 1.25 in Dimension - Body Width inch 1.18 in Dimension - Bolt Size fraction 5/8 Dimension - D inch 150 in Dimension - Height fraction 1-3/4 1.94 in Dimension - Height inch Dimension - L Length Overall 100 mm

Dimension - Length Overall 3.94 in

Dimension - Nut Width inch 1.35 in 0.55 in Dimension - P inch Dimension - Threads per inch

#### **Conductor Related**

Conductor - Copper Solid Size 1 AWG;1/0 AWG;2/0 AWG;3/0

AWG;4/0 AWG

Conductor - Copper Solid Size 1 AWG-4/0 AWG

Conductor - Copper Str Size 1 AWG;1/0 ;2/0 AWG;3/0

AWG;4/0 AWG 1 AWG-4/0 AWG

Conductor - Copper Str Size

Range

Physical Attribute - Number of 2 Conductors Accommodated

# **Certifications and Compliance**

Certification - CSA Approved Certification - ETL No Certification - UL Listed Direct Yes

Burial

Certification - UL Recognized Certification - cULus Nο Industry Standard(s) **UL467** Standards - Industry UL467

Standards Met

Standards - RoHS Compliance

Status

**UL** Listed Yes

#### Logistics

Minimum Pack Quantity

#### **Product Assets**

3D Models - K2C28B1 MODEL-PDF 3D Models - K2C28B1\_MODEL-IGES 3D Models - K2C28B1\_MODEL-STEP Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Sales Drawings - SD..055917

