

# KC23, SERVIT POST Mechanical Connector, Cable to Flat

By Burndy Catalog # KC23

Mechanical SERVIT POST™ Connector; Cable to Flat, 8-2 AWG (Str) / 10-1 AWG (Sol), 3/8" Stud; body height: 1.05"



# **Application**

For Direct Burial Applications And Used To Ground One Or Two Cables To Steel Structures, Fence Posts, Transformers, Also Used To Tap One Or Two Cables From Bus Bar

#### General

EU RoHS Indicator Yes

Material Bronze, Leaded, Commercial

Plated N

Plating Type Unplated
Stud Installation Torque inch 280 LBS/in

pounds

Sub BrandSERVIT POSTTrade NameSERVIT POST™TypeKC and K2C SeriesUPC781810255353UPC 12 Digit7818102553533

#### **Dimensions**

Dimension - B Length fraction 15/32 in Dimension - Body Width inch 0.62 in Dimension - Bolt Size fraction 3/8 Dimension - D inch 0.63 in Dimension - Height fraction Dimension - Length Overall 1.67 in inch Dimension - Nut Width inch 0.81 in Dimension - P inch 0.32 in Dimension - Threads per inch

### **Conductor Related**

Conductor - Copper Solid Size 10 AWG;9 AWG;8 AWG;7

AWG;6 AWG;5 AWG;4 AWG;3

AWG;2 AWG;1 AWG

8 AWG-2 AWG

Conductor - Copper Solid Size 10 AWG-1 AWG

Range

Conductor - Copper Str Size 8 AWG;7 AWG;6 AWG;5

AWG;4 AWG;3 AWG;2 AWG

Conductor - Copper Str Size

Range

Physical Attribute - Number of 1 Conductors Accommodated

Tota

## **Certifications and Compliance**

Certification - CSA Approved No Certification - ETL No Certification - UL Listed Direct Yes

Burial

Certification - UL Recognized No
Certification - cULus No
Industry Standard(s) UL467
Standards - Industry UL467

Standards Met

Standards - RoHS Compliance EX

Status

UL Listed Yes

#### Logistics

Carton Quantity 50
Minimum Pack Quantity 1
Pallet Quantity 59400

#### **Product Assets**

3D Models - KC23\_MODEL-IGES 3D Models - KC23\_MODEL-STEP 3D Models - KC23\_MODEL-PDF Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Sales Drawings - SD..055917

