

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## **KL201 A:6, B:6 Alu Comp Splice** *Abb Installation Products, Inc*

Catalog Number	KL201		
Manufacturer	Abb Installation Products, Inc		
Description	Aluminum 3-1/2 Inch Service Entrance Compression Splice For Wire Range - End A: 6 STR., 6 STR. Compact, Blue, End B: 6 STR., 6 STR. Compact, Blue, Die: 840. For AI to AI and AI to Cu Conductors.		
Weight per unit	0.2110 (lbs/each)		
Product Category	Large Terminals & Connectors		
Features			
connection	Compression		
insulation	None		
Material	Aluminum		
Number of Conductors	2		
<b>Dimensions and Weight</b>			
Size	3-1/2 Inch		
Descriptions			
Description	A:6,B:6 ALU COMP SPLICE		
extra long description	ABB KL20-1 AL SERVENTR SPLICE A:6 B		
Long Description	Aluminum 3-1/2 Inch Service Entrance Compression Splice for Wire Range - End A: 6 Str., 6 Str. Compact, Blue, End B: 6 Str., 6 Str. Compact, Blue, Die: 840. For AL to AL and AL to CU Conductors.		
Product Type	Al Serventr Splice A:6 B:4/0 3.5		
Special Features	Splices large conductors required for commercial service, use as low cost reducing sleeve. All sizes can be installed with popular mechanical and hydraulic tools. Center stop assures proper conductor positioning. Quick identifications with color-coded foi caps		
Manufacturer Information			
Brand	Blackburn Mechanical		
GTIN	00783786050000		
Manufacturers Part Number	KL20-1		
LIPC.	783786050000		

#### Mar

Brand	Blackburn Mechanical
GTIN	00783786050000
Manufacturers Part Number	KL20-1
UPC	783786050000

### **Taxonomies, Classifications, and Categories**

Category Description	Comp & Mech Lugs and Butt Splices
Туре	Compression Splice Service Entrance



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

1100	100	$\mathbf{n}$
יוגים	K AN	
Pac	Nuu	ши

Carton	25	
Package	250	
Weight Per each	0.211	

### Uses, Certifications, and Standards

Application	For Combinations of Aluminum-to-Aluminum and Aluminum-to-Copper Conductors	
environmental conditions	All Seasons / Conditions	
Mounting	None	
standard	Passes the requirements of ANSI C119.4	