


## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941

We Deliver...Lower Cost, Quality Products, & Personal Service





## KLPC2000 2000A 600V TD Class L Fuse

Catalog Number	KLPC2000
Manufacturer	Littelfuse
Description	KLPC Series Powr-Pro™ Fuses Provide Ideal Overcurrent
·	Protection For Circuits From 200 Through 6000 Amperes. KLPC

Performance Meet or Exceed The Most Stringent Project Specifications: 99.9% Pure Silver Links, Silver-Plated Copper End Bells, Glass-Reinforced Melamine Bodies, O-Ring Seals Between Body and End Bells, and Granular Quartz Fillers. KLPC Series Powr-Pro<sup>™</sup> Fuses Are The Only UI Listed Class L Fuses That

Series Powr-Pro™ Fuses Specification-Grade Construction and

Provide A Minimum Of Ten Seconds Tim

Weight per unit	8.3 (lbs/each)	
Product Category	Current Limiting	

**Features** 

2k amperage rating

**Descriptions** 

Description	2000A 600V TD CLASS L FUSE
extra long description	L-FSE KLPC2000 FUS 600V T/D CLASS L
Long Description	KLPC series POWR-PRO™ fuses provide ideal overcurrent protection for circuits from 200 through 6000 amperes. KLPC series POWR-PRO™ fuses specification-grade construction and performance meet or exceed the most stringent project specifications: 99.9% pure silver links, silver-plated copper end bells, glass-reinforced melamine bodies, O-ring seals between body and end bells, and granular quartz fillers. KLPC series POWR-PRO™ fuses are the only UL listed Class L fuses that provide a minimum of ten seconds tim

Product Type Fus 600V T/D Class L 2000a

Special Features **Current-limiting** 

**Manufacturer Information** 

Brand	Littelfuse
GTIN	00079458301120
Manufacturers Part Number	KLPC2000
sub brand	POWR-PRO
UPC	079458301120

**Taxonomies, Classifications, and Categories** 

Category Description	Fuses & Fuse Accessories
Туре	Time-Delay



## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

1
8.3
Switchboard Mains
Standard 248-10 UL Listed/CSA