ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



KLU800 800A 600V TD Class L Fuse

Bussmann Fuses

Catalog Number	KLU800
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class L Fuse, Klu, Time-Delay, Current Limiting Fuse, 800 A, Bladable Fuse, Interrupting Rating Of 200 Ka, 600 Vac
Weight per unit	3.8 (lbs/each)
Product Category	Current Limiting

Features

amperage rating	800
connection	Bolted Blade End X Bolted Blade End
dimensions	8.6300 IN X 2.5000 IN X 2.5000 IN
Fuse Class	Class L
interrupt rating	200 kAIC at 600 Vac
Response Time	5 sec at 500%
Voltage Rating	600 V

Dimensions and Weight

Size	2.50 In Diameter X 8.63 In Length

Descriptions

Description	800A 600V TD CLASS L FUSE
extra long description	BUS KLU-800 LIMITRON TIME DELAY FUS
Features	Bussmann's broad line of UL Class L fuses includes the KRP-C-SP Low-Peak family of fuses offering unsurpassed dual-element, current-limiting, time-delay performance and interrupting ratings of 300kA RMS Sym. Complementing the Low-Peak family are our Limitron products offering both Fast-acting and economical time-delay performance in our KTU, KLU, and KRP-CL products
Long Description	Eaton Bussmann Series Class L fuse, KLU, time-delay, current limiting fuse, 800 A, bladable fuse, interrupting rating of 200 kA, 600 Vac
Product Type	Limitron Time Delay Fuse
Special Features	Non-Indicating

Manufacturer Information

Brand	Eaton
GTIN	00051712135054
Manufacturers Part Number	KLU-800
UPC	051712135054

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSE

Packaging

Carton	1
Weight Per each	3.75

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
Mounting	Bolt-on
standard	RoHS Compliant,CE Marked