Specifications



Low-PEAK Unser rectario Data rectario Data en entration Data entration Data en entration Data entration Data

Eaton KRP-C-800SP

Eaton Bussmann Series Class L fuse, KRP-C, time-delay, current limiting fuse, 800 A, interrupting rating of 300 kA at 600 Vac and 100 kA at 300 Vdc

General specifications Eaton Bussmann series **PRODUCT NAME** KRP-C fuse **CATALOG NUMBER** KRP-C-800SP UPC 051712605083 PRODUCT 8.63 in LENGTH/DEPTH **PRODUCT HEIGHT** 2.53 in **PRODUCT WIDTH** 2.53 in **PRODUCT WEIGHT** 0.001 lb WARRANTY Not Applicable CE Marked COMPLIANCES **RoHS** Compliant



Electrical rating	
AMPERAGE RATING	800 A
INTERRUPT RATING	300 kAIC at 600 Vac 100 kA at 300 kAIC Vdc
RESPONSE TIME	4 sec at 500%
VOLTAGE RATING	600 Vac, 300 Vdc

General information	
CLASS	Class L
CONNECTION	Bolted blade end x bolted blade end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Small footprint

Physical details	
PACKAGING TYPE	Standard

Resources **Bussmann Full Line** Catalog CATALOGS Low Voltage Branch Circuit Fuse Chapter Eaton Bussmann EU **CERTIFICATION REPORTS** Declaration of conformity <u>93-68-EEC2006</u> COMPLIANCE **RoHS Search Tool** INFORMATION **Bussmann series MULTIMEDIA Fuseology** Bussmann series KRP-C **TECHNICAL DATA SHEETS** 601 to 2000A Class L fuse data sheet No. 1008

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.



Specifications



Low-PEAK Unser rectario Data rectario Data en entration Data entration Data en entration Data entration Data

Eaton KRP-C-800SP

Eaton Bussmann Series Class L fuse, KRP-C, time-delay, current limiting fuse, 800 A, interrupting rating of 300 kA at 600 Vac and 100 kA at 300 Vdc

General specifications Eaton Bussmann series **PRODUCT NAME** KRP-C fuse **CATALOG NUMBER** KRP-C-800SP UPC 051712605083 PRODUCT 8.63 in LENGTH/DEPTH **PRODUCT HEIGHT** 2.53 in **PRODUCT WIDTH** 2.53 in **PRODUCT WEIGHT** 0.001 lb WARRANTY Not Applicable CE Marked COMPLIANCES **RoHS** Compliant



Electrical rating	
AMPERAGE RATING	800 A
INTERRUPT RATING	300 kAIC at 600 Vac 100 kA at 300 kAIC Vdc
RESPONSE TIME	4 sec at 500%
VOLTAGE RATING	600 Vac, 300 Vdc

General information	
CLASS	Class L
CONNECTION	Bolted blade end x bolted blade end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Small footprint

Physical details	
PACKAGING TYPE	Standard

Resources **Bussmann Full Line** Catalog CATALOGS Low Voltage Branch Circuit Fuse Chapter Eaton Bussmann EU **CERTIFICATION REPORTS** Declaration of conformity <u>93-68-EEC2006</u> COMPLIANCE **RoHS Search Tool** INFORMATION **Bussmann series MULTIMEDIA Fuseology** Bussmann series KRP-C **TECHNICAL DATA SHEETS** 601 to 2000A Class L fuse data sheet No. 1008

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

