



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

5018 W Main Street
74701-0000, OK Durant
Phone: 580-745-5448
Fax: 580-745-5449



KSU34 400-500 Split Bolt Conn

Burndy LLC

Catalog Number	KSU34
Manufacturer	Burndy LLC
Description	Tin-Plated, High Strength Copper Alloy Servit With Spacer. Spacer Separates Dissimilar Conductors and Provides Long Contact Length That Prevents High Pressure Point Contacts Between Run and Tap Conductors, 3.12 In L.
Weight per unit	1.1 (lbs/each)
Product Category	Large Terminals & Connectors

Features

Material	Copper
pallet quantity	1296

Descriptions

Description	400-500 SPLIT BOLT CONN
extra long description	BUR KSU34 SERVIT UNIV 400-500
Long Description	Tin-plated, high strength copper alloy SERVIT with spacer. Spacer separates dissimilar conductors and provides long contact length that prevents high pressure point contacts between run and tap conductors, 3.12 IN L.
Product Type	Mechanical
Special Features	Features: Tin-Plated, High Strength Copper Alloy SERVIT With Spacer, Spacer Separates Dissimilar Conductors And Provides Long Contact Length That Prevents High Pressure Point Contacts Between Run And Tap Conductors, Use Of PENETROX Joint Compound Recommended With Aluminum And ACSR, Installation Torque: 825 IN-LB, Conductor Type: Run: ACSR, 5005, AAAC, Commercial Stranded Aluminum, Commercial Stranded And Solid Copper, Tap: ACSR, 5005, AAAC, Commercial Stranded Aluminum, Commercial Stranded And Solid Copper

Manufacturer Information

Brand	BURNDY
GTIN	00781810037102
Manufacturers Part Number	KSU34
UPC	781810037102

Taxonomies, Classifications, and Categories

Category Description	SPLIT BOLTS
Type	KSU, Universal



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

5018 W Main Street
74701-0000, OK Durant
Phone: 580-745-5448
Fax: 580-745-5449

Packaging

Carton	1
Package	12
Weight Per each	1.114

Uses, Certifications, and Standards

Application	For All Combinations Of Copper, Aluminum, ACSR, AAAC, 5005, And Steel
standard	TAA Compliant (All status valid till December 2024)