

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



KVSU28 lks-4/0 Tinned Cu 2-Bolt Split Bolt Conn Burndy LLC

Catalog Number	KVSU28
Manufacturer	Burndy LLC
Description	Tin-Plated Copper Alloy Connector With Tin Plated Silicon Bronze
	Hardware. Spacer Bar Separates Dissimilar Conductors and
	Provides Long Contact Length, Tightening Torque:250 In -LB, Wrench Size:9/16 Cross Flats.
Waight par upit	
Weight per unit Product Category	0.3800 (lbs/each) Large Terminals & Connectors
0.1	Large reminals & connectors
Features	
Material	Copper;Copper alloy
Material, Color, and Finish	
Finish	Tinned
Descriptions	
Description	IKS-4/0 TINNED CU 2-BOLT SPLIT BOLT CONN
extra long description	BUR KVSU28 UNIV OKLIP 1/0-4/0/6-4/0
Long Description	Tin-plated copper alloy connector with tin plated silicon bronze
	hardware. Spacer bar separates dissimilar conductors and
	provides long contact length,Tightening torque:250 in -lb,wrench
	size:9/16 cross flats.
Product Type	Mechanical
Special Features	Features: Compact, Tin Plated High Strength Copper Alloy
	Two-Piece Connector With Spacer And Tin-Plated Silicon Bronze
	DURIUM Hardware, Recommended For Heavy Duty Connections,
	Spacer Separates Dissimilar Conductors And Provides Long Contact Length, Neoprene Ring Prevents Loss Of Shorter Bolt
	During Installation, Longer Peened Bolt Permits Swivel Action For
	Easier Installation, Use Of PENETROX Joint Compound
	Recommended With Aluminum And ACSR, Conductor Type: Run
	And Tap: Commercial Stranded Copper, Commerc
Manufacturer Information	
Brand	BURNDY
	00701010001000
Manufacturers Part Number	KVSU28
sub brand	OKLIP
UPC	
Taxonomies, Classifications, and Cate	
Category Description	
Туре	KVS, Compact, Universal



$E_{\text{LLIOTT}} E_{\text{LECTRIC}} S_{\text{UPPLY}}$

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	-
Doole	aina
Packa	
	- 3 3

i ackaying	
Carton	1
Weight Per each	0.38
Uses, Certifications, and Standards	
Application	For All Combinations Of Copper, Aluminum, ACSR, AAAC And 5005