

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



L2N #2 1/2" 2 Hole Long Barrel Compression Lug *Nsi Industries*

Catalog Number	L2N
Manufacturer	Nsi Industries
Description	2 Hole Long Barrel Copper Compression Lug 2 Awg - 1/2" Bolt Long Barrel Copper Compression Lugs Are Produced From High Conductivity Copper Tubing. Allows Easy Inspection Of The Termination to Assure Complete Cable Insertion. Tin-Plated to Provide Corrosion and Low Contact Resistance. Marked With Die Index and Color Coded. Listed For 35KV Maximum When Properly Installed. Rated 600V. Culus 486A/B Listed. UL467 Listed On Sizes 6 Awg - 3/0 Awg. Temperature Rating 90 Degrees C.
Weight per unit	
Product Category	
Features	
Cable Size	# 2 AWG (STR)
Material	Copper
Number of Holes	2
Stud Size	1/2
Voltage Rating	600 V
Warranty	1 YEAR
Material, Color, and Finish	
Color	Brown
Finish	Tin Plated
Dimensions and Weight	
Size	L=4.25 - W=.810 - OD=.420 - ID=.310



standard

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Descript	ions	
-	ription	#2 1/2" 2 HOLE LONG BARREL COMPRESSION LUG
	ilong description	NSI L2N CU CMP Lug Long 2 AWG Nema
Feat		2 Hole Long Barrel Copper Compression Lug 2 AWG - 1/2" Bolt
		Long Barrel Copper Compression Lugs are produced from high
		conductivity copper tubing. Allows easy inspection of the
		termination to assure complete cable insertion. Tin-plated to
		provide corrosion and low contact resistance. Marked with die
		index and color coded. Listed for 35KV maximum when properly
		installed. Rated 600V. cULus 486A/B Listed. UL467 Listed on sizes
		6 AWG - 3/0 AWG. Temperature rating 90 degrees C.
Long	Description	2 Hole Long Barrel Copper Compression Lug 2 AWG - 1/2" Bolt
	Long Barrel Copper Compression Lugs are produced from high	
		conductivity copper tubing. Allows easy inspection of the termination to assure complete cable insertion. Tin-plated to
		provide corrosion and low contact resistance. Marked with die
		index and color coded. Listed for 35KV maximum when properly
		installed. Rated 600V. cULus 486A/B Listed. UL467 Listed on sizes
		6 AWG - 3/0 AWG. Temperature rating 90 degrees C.
Prod	uct Type	Cu CMP Lug Long 2 Awg Nema MTG Spac
Spec	ial Features	# 2 AWG (STR) - 1/2 Mounting Holes - 1 3/4 Hole Spacing
Manufac	cturer Information	
Bran		NSi
GTIN		00662381035066
UPC		662381035066
Taxonon	nies, Classifications, and Cat	egories
	gory Description	9
Туре		Long Barrel - Two Hole
Packagir	na	
Carto	•	1
Pack	age	50
Weig	ht Per each	0.09
Uses. Ce	rtifications, and Standards	
	ication	Terminate, Splice, Tap Power Connectors
	onmental conditions	90 C
Mou	nting	1/2 Mounting Holos

UL486A/B, UL467 (8 AWG -3/0 AWG)