# LC2201

In-Wall 1500W RF Switch



## What This Product Does

The RF Smart Lighting Control system provides a wireless lighting solution for today's integrated home. With a system maximum of (100) end-points, this solution can effortlessly scale for any project.

This in-wall switch can easily control any non-dimmable load or device.

## Features

**Ultra-reliable** with Legrand's patented Radio Frequency technology

**Easy installation** using existing electrical wiring

**Simple setup** and device pairing

**Complete control** via Lighting Control app, Amazon Alexa or the Google Assistant

**Seamless integration** with IP drivers for Control4, URC, RTI, Elan, and Crestron

**Convenient grouping** for single-touch control of customized lighting scenes

**Effortless automation** by time of day or by predetermined preferences

**Flawless fit and finish** as part of the radiant® Collection

*Part of the* radiant® *collection*

## About the Collection

The radiant® Collection is a step up from the standard with simple, classic options in wiring devices, home automation controls and screw-less wall plates that complement today's homes.

## LC2201-XX Technical Specifications

| General Information | |
|---|---|
| Colors Available (XX) | WH = White; LA = Light Almond; NI = Nickel |

| Product Information | |
|---|---|
| Product Dimensions | 4.8"D x 2.5"H x 3.0"W |
| Weight | 0.34 lbs |
| Unit Package Dimensions | 2.5"D x 4.8"H x 3.1"W |
| Case Package Quantity | 20 |
| Case Package Dimensions | 6.7"D x 9.8" H x 13.78"W |

| Technical Information | |
|---|---|
| Radio | 900MHz Top Dog™ Radio Frequency |
| System Range | 100ft between devices (expands up to 300ft between devices when used with (2) MRR2G) |
| AC Voltage Input | 120V |
| Rating | Full 15A resistive, 1/2 HP |
| Frequency | 60Hz |
| Terminal | Terminals accommodate #12 and #14 AWG stranded and copper wire. |
| Humidity | 0-90% relative humidity, non-condensing |
| Operating Temperature | 32°~109.4°F (0°~43°C) |

### COMPATIBILITY

- Works with Alexa and the Google Assistant
- IP-based drivers for seamless integration with Control4, Elan, RTI and URC
- Serial-based driver for Crestron

### COMPLIANCE

- cULus Listed
- RoHS Compliant
- FCC Class B Part 15

### SYSTEM REQUIREMENTS

- LC7001 (Whole-House Lighting Controller)
- Neutral wire required
- LC2203 (required for 3-way applications)
- radiant® Screwless Wall Plate (not included)

### WARRANTY

- One-year limited warranty



**USA** 866.977.3901 • **CANADA** 877.345.4329
av.resi.sales.operations@legrand.com
legrandav.com ©2019 Legrand AV Inc.

# LC2201

In-Wall 1500W RF Switch



## What This Product Does

The RF Smart Lighting Control system provides a wireless lighting solution for today's integrated home. With a system maximum of (100) end-points, this solution can effortlessly scale for any project.

This in-wall switch can easily control any non-dimmable load or device.

## Features

**Ultra-reliable** with Legrand's patented Radio Frequency technology

**Easy installation** using existing electrical wiring

**Simple setup** and device pairing

**Complete control** via Lighting Control app, Amazon Alexa or the Google Assistant

**Seamless integration** with IP drivers for Control4, URC, RTI, Elan, and Crestron

**Convenient grouping** for single-touch control of customized lighting scenes

**Effortless automation** by time of day or by predetermined preferences

**Flawless fit and finish** as part of the radiant® Collection

*Part of the* radiant® *collection*

## About the Collection

The radiant® Collection is a step up from the standard with simple, classic options in wiring devices, home automation controls and screw-less wall plates that complement today's homes.

## LC2201-XX Technical Specifications

| General Information | |
|---|---|
| Colors Available (XX) | WH = White; LA = Light Almond; NI = Nickel |

| Product Information | |
|---|---|
| Product Dimensions | 4.8"D x 2.5"H x 3.0"W |
| Weight | 0.34 lbs |
| Unit Package Dimensions | 2.5"D x 4.8"H x 3.1"W |
| Case Package Quantity | 20 |
| Case Package Dimensions | 6.7"D x 9.8" H x 13.78"W |

| Technical Information | |
|---|---|
| Radio | 900MHz Top Dog™ Radio Frequency |
| System Range | 100ft between devices (expands up to 300ft between devices when used with (2) MRR2G) |
| AC Voltage Input | 120V |
| Rating | Full 15A resistive, 1/2 HP |
| Frequency | 60Hz |
| Terminal | Terminals accommodate #12 and #14 AWG stranded and copper wire. |
| Humidity | 0-90% relative humidity, non-condensing |
| Operating Temperature | 32°~109.4°F (0°~43°C) |

### COMPATIBILITY

- Works with Alexa and the Google Assistant
- IP-based drivers for seamless integration with Control4, Elan, RTI and URC
- Serial-based driver for Crestron

### COMPLIANCE

- cULus Listed
- RoHS Compliant
- FCC Class B Part 15

### SYSTEM REQUIREMENTS

- LC7001 (Whole-House Lighting Controller)
- Neutral wire required
- LC2203 (required for 3-way applications)
- radiant® Screwless Wall Plate (not included)

### WARRANTY

- One-year limited warranty



**USA** 866.977.3901 • **CANADA** 877.345.4329
av.resi.sales.operations@legrand.com
legrandav.com ©2019 Legrand AV Inc.