

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Catalog Number	LCA3012X
Manufacturer	Panduit Corporation
Description	The LCA3/0-12-X Tin-Plated Copper Compression Lug, One-Hole, Standard Barrel, Has Color-Coded Barrels Marked With Panduit and Specified Competitor Die Index Numbers For Proper Crimp Die Selection. An Inspection Window Aids to Visually Assure Full Conductor Insertion, and The Tin-Plate Material Helps to Inhibit Corrosion. UI Listed and Csa Certified to 35 KV and Temperature Rated to 90°C.
Weight per unit	1.0 (lbs/each)
Product Category	Large Terminals & Connectors
Features	
Material	Tin-Plated Copper
media	Yes
Number of Holes	1
Stud Size	
Material, Color, and Finish	
Color	Orange
<b>Dimensions and Weight</b>	
Size	3/0 AWG Code
Descriptions	
Description	3/0AWG 1HOLE LUG
extra long description	PAN LCA3/0-12-X Pan-Lug™ LCA3/0-12-
Long Description	The LCA3/0-12-X Tin-Plated Copper Compression Lug, one-hole, standard barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. An inspection window aids to visually assure full conductor insertion, and the tin-plate material helps to inhibit corrosion. UL Listed and CSA Certified to 35 KV and temperature rated to 90°C.
Product Type	Pan-Lug™ LCA3/0-12-X Comp. Lug, 3/0, Tin PLT Copper, STRT, O
Special Features	Consult cable manufacturer for voltage stress relief instructions

## **Manufacturer Information**

Brand	PANDUIT
GTIN	00074983900367
Manufacturers Part Number	LCA3/0-12-X
UPC	074983900367

with applications greater than 2000 V



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

65-13

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories		
	Comp & Mech Lugs and Butt Splices	
Туре	Compression Lug	
Packaging		
Carton	10	
Package	20	
Weight Per each	1	
Uses, Certifications, and Standard	ds	
Mounting	1-3/16	
standard	UL listed to 486A-486B File #E52164 and CSA certified C22.2 No.	