



LCA35012X 350MCM 1HOLE Lug

Panduit Corporation

Catalog Number	LCA35012X
Manufacturer	Panduit Corporation
Description	The LCA350-12-X Tin-Plated Copper Compression Lug, One-Hole, Standard Barrel, Has Color-Coded Barrels Marked With Panduit and Specified Competitor Die Index Numbers For Proper Crimp Die Selection. An Inspection Window Aids to Visually Assure Full Conductor Insertion, and The Tin-Plate Material Helps to Inhibit Corrosion. UL Listed and CSA Certified to 35 KV and Temperature Rated to 90°C.
Weight per unit	1.0 (lbs/each)
Product Category	Large Terminals & Connectors

Features

Material	Copper
media	Yes
Number of Holes	1
Stud Size	1/2

Material, Color, and Finish

Color	Red
-------	-----

Dimensions and Weight

Size	350 kcmil Code
------	----------------

Descriptions

Description	350MCM 1HOLE LUG
extra long description	PAN LCA350-12-X Pan-Lug™ LCA350-12-
Long Description	The LCA350-12-X Tin-Plated Copper Compression Lug, one-hole, standard barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. An inspection window aids to visually assure full conductor insertion, and the tin-plate material helps to inhibit corrosion. UL Listed and CSA Certified to 35 KV and temperature rated to 90°C.
Product Type	Pan-Lug™ LCA350-12-X Comp. Lug, 350, Tin PLT Copper, STRT, O
Special Features	Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 V



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

10440 Airline Highway
70816-0000, LA Baton Rouge
Phone: 225-292-7746
Fax: 225-292-7840

Manufacturer Information

Brand	PANDUIT
GTIN	00074983900558
Manufacturers Part Number	LCA350-12-X
UPC	074983900558

Taxonomies, Classifications, and Categories

Category Description	Comp & Mech Lugs and Butt Splices
Type	Compression Lug

Packaging

Carton	10
Package	20
Weight Per each	1

Uses, Certifications, and Standards

Mounting standard	1-1/2
	UL Listed to 486A-486B File #E52164, NEBS Level 3, ABS