

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LCA414L 4AWG 1HOLE Lug Panduit Corporation

Catalog Number	LCA414L
Manufacturer	Panduit Corporation
Description	The LCA4-14-L Tin-Plated Copper Compression Lug, One-Hole, Standard Barrel, Has Color-Coded Barrels Marked With Panduit and Specified Competitor Die Index Numbers For Proper Crimp Die Selection. An Inspection Window Aids to Visually Assure Full Conductor Insertion, and The Tin-Plate Material Helps to Inhibit Corrosion. UI Listed and Csa Certified to 35 KV and Temperature Rated to 90°C.
Weight per unit	0.0260 (lbs/each)
Product Category	
Features	, and the second
Material	Copper
media	Yes
Number of Holes	
Stud Size	1/4
Material, Color, and Finish Color	Gray
1010	Oray
Dimensions and Weight	#4 #2 AVAC Codo CTD #2 AVAC Codo COL
Size	#4 — #3 AWG Code STR, #2 AWG Code SOL
Descriptions	
Description	4AWG 1HOLE LUG
extra long description	PAN LCA4-14-L Pan-Lug™ LCA4-14-L Co
Long Description	The LCA4-14-L Tin-Plated Copper Compression Lug, one-hole, standard barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. An inspection window aids to visually assure full conductor insertion, and the tin-plate material helps to inhibit corrosion. UL Listed and CSA Certified to 35 KV and temperature rated to 90°C.
Product Type	Pan-Lug™ LCA4-14-L Comp. Lug, 4, Tin PLT Copper, STRT, One 1
Special Features	Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 V
Manufacturer Information	
Brand	PANDUIT
GTIN	00074983900114
Manufacturers Part Number	LCA4-14-L
UPC	074983900114



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

65-13

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories	
Category Description	Comp & Mech Lugs and Butt Splices
Туре	
Packaging	
Carton	50
Weight Per each	0.026
Uses, Certifications, and Standards	
Mounting	7/8
standard	UL listed to 486A-486B File #E52164 and CSA certified C22.2 No.