

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LCA438L 4AWG 1HOLE Lug *Panduit Corporation*

Catalog Number	LCA438L
Manufacturer	Panduit Corporation
Description	The LCA4-38-L Tin-Plated Copper Compression Lug, One-Hole, Standard Barrel, Has Color-Coded Barrels Marked With Panduit and Specified Competitor Die Index Numbers For Proper Crimp Die Selection. An Inspection Window Aids to Visually Assure Full Conductor Insertion, and The Tin-Plate Material Helps to Inhibit Corrosion. UI Listed and Csa Certified to 35 KV and Temperature Rated to 90°C.
Weight per unit	
Product Category	·
	Lui ge Terrimiuis & connectors
eatures Material	Connor
media	Copper Yes
Number of Holes	1
Stud Size	3/8
	3, 0
laterial, Color, and Finish Color	Cray
	Gray
imensions and Weight	#4
Size	#4 — #3 AWG Code STR, #2 AWG Code SOL
escriptions	
Description	4AWG 1HOLE LUG
extra long description	PAN LCA4-38-L Pan-Lug™ LCA4-38-L Co
Long Description	The LCA4-38-L Tin-Plated Copper Compression Lug, one-hole, standard barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. An inspection window aids to visually assure full conductor insertion, and the tin-plate material helps to inhibit corrosion. UL Listed and CSA Certified to 35 KV and temperature rated to 90°C.
Product Type	Pan-Lug™ LCA4-38-L Comp. Lug, 4, Tin PLT Copper, STRT, One 3
Special Features	Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 V
lanufacturer Information	
Brand	PANDUIT
GTIN	00074983900138
Manufacturers Part Number	LCA4-38-L
UPC	074983900138



Weight Per each

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories		
Category Description	Comp & Mech Lugs and Butt Splices	
Туре	Compression Lug	
Packaging Carton	50	

Uses, Certifications, and Standards	
Mounting	7/8
standard	UL listed to 486A-486B File #E52164 and CSA certified C22.2 No.

65-13