

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LCA810L Panduit LCA8-10-L Copper *Panduit Corporation*

Catalog Number	LCA810L
Manufacturer	Panduit Corporation
Description	The LCA8-10-L Tin-Plated Copper Compression Lug, One-Hole, Standard Barrel, Has Color-Coded Barrels Marked With Panduit and Specified Competitor Die Index Numbers For Proper Crimp Die Selection. An Inspection Window Aids to Visually Assure Full Conductor Insertion, and The Tin-Plate Material Helps to Inhibit Corrosion. UI Listed and Csa Certified to 35 KV and Temperature Rated to 90°C.
Weight per unit	N/A
Product Category	Large Terminals & Connectors

Features

Material	Tin-Plated Copper	
media	Yes	
Number of Holes	1	
Stud Size	#10	

Material, Color, and Finish

Color	Red
UOIOI	R₽O
00101	INCO

Dimensions and Weight

Size	#8 AWG Code	
Size	πο Αννό σομε	

Descriptions

Description extra long description Long Description	PANDUIT LCA8-10-L COPPER PAN LCA8-10-L Pan-Lug™ LCA8-10-L Co The LCA8-10-L Tin-Plated Copper Compression Lug, one-hole, standard barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. An inspection window aids to visually assure full conductor insertion, and the tin-plate material helps to inhibit corrosion. UL Listed and CSA Certified to 35 KV and temperature rated to 90°C.
Product Type	Pan-Lug™ LCA8-10-L Comp. Lug, 8, Tin PLT Copper, STRT, One #
Special Features	Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 V

Manufacturer Information

Brand	PANDUIT
GTIN	00074983900008
Manufacturers Part Number	LCA8-10-L
UPC	074983900008



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomie	es, Classificat	ions, and	Categories
T			C =

Туре	Compression Lug	
Packaging		
Carton	1	
Package	50	
Weight Per each	0	
Uses, Certifications, and Standard		
Mountina	5/8	
standard	C22.2 No. 65-13, 486A-486B File #E52164	