

## ELLIOT ELECTRIC SUPPLY No Deliver Cost Quality Products, & Personal Service 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## LCB2038X 2/0AWG 1HOLE Lug Panduit Corporation

Catalog Number Manufacturer Description	LCB2038X Panduit Corporation The LCB2/0-38-X Tin-Plated Copper Compression Lug, One-Hole,
·	Long Barrel, Has Color-Coded Barrels Marked With Panduit and Specified Competitor Die Index Numbers For Proper Crimp Die Selection. An Inspection Window Aids to Visually Assure Full Conductor Insertion, and The Tin-Plate Material Helps to Inhibit Corrosion. UI Listed and Csa Certified to 35 KV and Temperature Rated to 90°C.
Weight per unit	
Product Category	Large Terminals & Connectors
Features	
Material	Tin-Plated Copper
media	Yes
Number of Holes	
Stud Size	3/8
Material, Color, and Finish	
Color	Black
Dimensions and Weight	
Size	2/0 AWG Code
Descriptions	
Description	
extra long description	PAN LCB2/0-38-X Pan-Lug™ LCB2/0-38-
Long Description	The LCB2/0-38-X Tin-Plated Copper Compression Lug, one-hole, long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. An inspection window aids to visually assure full conductor insertion, and the tin-plate material helps to inhibit corrosion. UL Listed and CSA Certified to 35 KV and temperature rated to 90°C.
Product Type	Pan-Lug™ LCB2/0-38-X Comp. Lug, 2/0, Long, Tin PLT Copper, S
Special Features	Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 V
Manufacturer Information	
Brand	PANDUIT
GTIN	00074983901302
Manufacturers Part Number	LCB2/0-38-X
UPC	074983901302



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description	TERMINALS
Туре	Compression Lug
Packaging	
Carton	1
Package	50
Weight Per each	1.05
Uses, Certifications, and Standa	
Mounting	1-5/8
standard	C22.2 No. 65-13, 486A-486B File #E52164