



LCB2038X 2/0AWG 1HOLE Lug

Panduit Corporation

Catalog Number	LCB2038X
Manufacturer	Panduit Corporation
Description	The LCB2/0-38-X Tin-Plated Copper Compression Lug, One-Hole, Long Barrel, Has Color-Coded Barrels Marked With Panduit and Specified Competitor Die Index Numbers For Proper Crimp Die Selection. An Inspection Window Aids to Visually Assure Full Conductor Insertion, and The Tin-Plate Material Helps to Inhibit Corrosion. UL Listed and CSA Certified to 35 KV and Temperature Rated to 90°C.
Weight per unit	1.1 (lbs/each)
Product Category	Large Terminals & Connectors

Features

Material	Tin-Plated Copper
media	Yes
Number of Holes	1
Stud Size	3/8

Material, Color, and Finish

Color	Black
-------	-------

Dimensions and Weight

Size	2/0 AWG Code
------	--------------

Descriptions

Description	2/0AWG 1HOLE LUG
extra long description	PAN LCB2/0-38-X Pan-Lug™ LCB2/0-38-
Long Description	The LCB2/0-38-X Tin-Plated Copper Compression Lug, one-hole, long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. An inspection window aids to visually assure full conductor insertion, and the tin-plate material helps to inhibit corrosion. UL Listed and CSA Certified to 35 KV and temperature rated to 90°C.
Product Type	Pan-Lug™ LCB2/0-38-X Comp. Lug, 2/0, Long, Tin PLT Copper, S
Special Features	Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 V



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3520 S Sam Houston Pkwy East Suite 900
77047-0000, TX Houston
Phone: 281-412-7049
Fax: 281-412-7314

Manufacturer Information

Brand	PANDUIT
GTIN	00074983901302
Manufacturers Part Number	LCB2/0-38-X
UPC	074983901302

Taxonomies, Classifications, and Categories

Category Description	TERMINALS
Type	Compression Lug

Packaging

Carton	1
Package	50
Weight Per each	1.05

Uses, Certifications, and Standards

Mounting standard	1-9/16 C22.2 No. 65-13, 486A-486B File #E52164, ABS approved, NEBS Level 3
-------------------	---