

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



#### LD13T5HE48GC850D \*Discontinued\* 13W 120-277V 50K T5 Led Keystone Technologies

Manufacturer  Description  Linear Fluorescent Led Lamp, Linear, Instant Start Type; 45.19 Inch; UI (Canada and Us), UI, NSF/Ansi, EtI, DLC Approval; Food Equipment Application; 120 to 277 Volt Ac Voltage Rating; 0.82 Inch Diameter  Weight per unit Product Category  Shape & Circular Lamps  Features  Beam Spread Angle Current Rating 0.11 Amp at 120 Volt AC, 0.05 Amp at 277 Volt AC Glass Finish FROSTED Intensity 1800 LUMEN Item LED Lamp Voltage Rating 120 to 277 Volt AC Wattage 13 Watt  Material, Color, and Finish Base Type Color Rendering Index Color Temperature in Kelvin  Diameter Length 45.19 Inch  Descriptions  Additional Information Posscription Posscription Posscription Long Description Long Description Linear Fluorescent Straight, U-Shape & Circular Lamps Possible Time Application; 120 to 277 Volt AC Voltage Rating Time Application; 120 to 277 Volt AC Voltage Rating Time Application; 120 to 277 Volt AC Voltage Rating Time Application; 120 to 277 Volt AC Voltage Rating Time Application; 120 to 277 Volt AC Voltage Rating; 0.82 INCH Length Diameter Description Length Diameter Length Diameter Description Length Diameter Length Diameter Description Length Diameter Description Length Diameter Length Diameter Description Descript		10.00000
Description  Linear Fluorescent Led Lamp, Linear, Instant Start Type; 45.19 Inch; UI (Canada and Us), UI, NSF/Ansi, EtI, DLC Approval; Food Equipment Application; 120 to 277 Volt Ac Voltage Rating; 0.82 Inch Diameter  Weight per unit 0.5160 (lbs/each) Product Category Shape & Circular Lamps  Features  Beam Spread Angle 240 Degree Current Rating 0.11 Amp at 120 Volt AC, 0.05 Amp at 277 Volt AC Glass Finish FROSTED Intensity 1800 LUMEN Item LED Lamp Voltage Rating 120 to 277 Volt AC Wattage 13 Watt  Material, Color, and Finish Base Type Color Rendering Index Color Temperature in Kelvin 5000  Dimensions and Weight Diameter Length 45.19 Inch  Descriptions Additional Information ROHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumper Watt; Visible Light Area 325 Degree; Temperature -4 to 11: Deg F Commodity Description Led Linear Fluorescent Straight, U-Shape & Circular Lamps Description - *DISCONTINUED** 13W 120-277V 50K T5 LED Long Description LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPI 45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC APPROVAL; FOOD EQUIPMENT APPLICATION; 120 T0 277 VOL' AC VOLTAGE RATING; 0.82 INCH DIAMETER	Catalog Number	LD13T5HE48GC850D
Inch; UI (Canada and Us), Uİ, NSF/Ansi, EtI, DLC Approval; Food Equipment Application; 120 to 277 Volt Ac Voltage Rating; 0.82 Inch Diameter  Weight per unit 0.5160 (Ibs/each) Product Category Shape & Circular Lamps  Features  Beam Spread Angle 240 Degree Current Rating 0.11 Amp at 120 Volt AC, 0.05 Amp at 277 Volt AC Glass Finish FROSTED Intensity 1800 LUMEN Item LED Lamp Voltage Rating 120 to 277 Volt AC Wattage 13 Watt  Material, Color, and Finish Base Type G5 Miniature 2-Pin Color Rendering Index 80 A Color Temperature in Kelvin 5000  Dimensions and Weight Diameter 0.82 INCH Length 45.19 Inch  Descriptions  Additional Information ROHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumper Watt; Visible Light Area 325 Degree; Temperature -4 to 11: Deg F Commodity Description Led Linear Fluorescent Straight, U-Shape & Circular Lamps Description *DISCONTINUED* 13W 120-277V 50K T5 LED Long Description LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPI 45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETI, DLC APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOL' AC VOLTAGE RATING; 0.82 INCH DIAMPETER		
Features  Beam Spread Angle 240 Degree Current Rating 0.11 Amp at 120 Volt AC, 0.05 Amp at 277 Volt AC Glass Finish FROSTED Intensity 1800 LUMEN Item LED Lamp Voltage Rating 120 to 277 Volt AC Wattage 13 Watt  Material, Color, and Finish Base Type G5 Miniature 2-Pin Color Rendering Index 80 A Color Temperature in Kelvin 5000  Dimensions and Weight Diameter 0.82 INCH Length 45.19 Inch  Descriptions  Additional Information ROHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumper Watt; Visible Light Area 325 Degree; Temperature -4 to 11: Deg F Commodity Description Led Linear Fluorescent Straight, U-Shape & Circular Lamps Description Description LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPI 45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC APPROVAL; FOOD EQUIPMENT APPLICATION: 120 TO 277 VOL' AC VOLTAGE RATING; 0.82 INCH DIAMETER	Description	Inch; UI (Canada and Us), UI, NSF/Ansi, EtI, DLC Approval; Food Equipment Application; 120 to 277 Volt Ac Voltage Rating; 0.82
Features  Beam Spread Angle 240 Degree Current Rating 0.11 Amp at 120 Volt AC, 0.05 Amp at 277 Volt AC Glass Finish FROSTED Intensity 1800 LUMEN Item LED Lamp Voltage Rating 120 to 277 Volt AC Wattage 13 Watt  Material, Color, and Finish Base Type G5 Miniature 2-Pin Color Rendering Index 80 A Color Temperature in Kelvin 5000  Dimensions and Weight Diameter 0.82 INCH Length 45.19 Inch  Descriptions Additional Information ROHS Compliant: Shatter Proof Coated Glass; Efficacy 139 Lumper Watt; Visible Light Area 325 Degree; Temperature -4 to 11: Deg F Commodity Description Led Linear Fluorescent Straight, U-Shape & Circular Lamps Description *DISCONTINUED* 13W 120-2777 V 50K T5 LED Long Description LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPI 45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOL: AC VOLTAGE RATING; 0.82 INCH DIAMETER	Weight per unit	0.5160 (lbs/each)
Beam Spread Angle Current Rating 0.11 Amp at 120 Volt AC, 0.05 Amp at 277 Volt AC Glass Finish FROSTED Intensity 1800 LUMEN Item LED Lamp Voltage Rating 120 to 277 Volt AC Wattage 13 Watt  Material, Color, and Finish Base Type Color Rendering Index 80 A Color Temperature in Kelvin  Diameter Length Diameter Length 45.19 Inch  Descriptions Additional Information Poescription Additional Proscription Led Linear Fluorescent Straight, U-Shape & Circular Lamps Description Long Description Linear Fluorescent Straight, U-Shape & Circular Lamps Description 277 Vol. AC	Product Category	Shape & Circular Lamps
Current Rating 0.11 Amp at 120 Volt AC, 0.05 Amp at 277 Volt AC Glass Finish FROSTED Intensity 1800 LUMEN Item LED Lamp Voltage Rating 120 to 277 Volt AC Wattage 13 Watt  Material, Color, and Finish Base Type G5 Miniature 2-Pin Color Rendering Index 80 A Color Temperature in Kelvin 5000  Dimensions and Weight Diameter 0.82 INCH Length 45.19 Inch  Descriptions Additional Information ROHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumper Watt; Visible Light Area 325 Degree; Temperature -4 to 11: Deg F Commodity Description Led Linear Fluorescent Straight, U-Shape & Circular Lamps Description *DISCONTINUED* 13W 120-277V 50K T5 LED Long Description LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPI 45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOLTACE VOLTAGE RATING; 0.82 INCH DIAMETER	Features	
Glass Finish FROSTED Intensity 1800 LUMEN Item LED Lamp Voltage Rating 120 to 277 Volt AC Wattage 13 Watt  Material, Color, and Finish Base Type G5 Miniature 2-Pin Color Rendering Index 80 A Color Temperature in Kelvin 5000  Dimensions and Weight Diameter 0.82 INCH Length 45.19 Inch  Descriptions Additional Information ROHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumper Watt; Visible Light Area 325 Degree; Temperature -4 to 11: Deg F Commodity Description Led Linear Fluorescent Straight, U-Shape & Circular Lamps Description *DISCONTINUED* 13W 120-277V 50K T5 LED Long Description LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPE 45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOLTACE VOLTAGE RATING; 0.82 INCH DIAMETER	Beam Spread Angle	240 Degree
Intensity 1800 LUMEN  Item LED Lamp  Voltage Rating 120 to 277 Volt AC  Wattage 13 Watt   Material, Color, and Finish  Base Type G5 Miniature 2-Pin  Color Rendering Index 80 A  Color Temperature in Kelvin 5000  Dimensions and Weight  Diameter 0.82 INCH  Length 45.19 Inch   Descriptions  Additional Information ROHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumper Watt; Visible Light Area 325 Degree; Temperature -4 to 11:  Deg F  Commodity Description Led Linear Fluorescent Straight, U-Shape & Circular Lamps  Description *DISCONTINUED* 13W 120-277V 50K T5 LED  Long Description LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPE 45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOLTACE RATING; 0.82 INCH DIAMETER	Current Rating	0.11 Amp at 120 Volt AC, 0.05 Amp at 277 Volt AC
Item LED Lamp  Voltage Rating 120 to 277 Volt AC  Wattage 13 Watt   Material, Color, and Finish  Base Type G5 Miniature 2-Pin  Color Rendering Index 80 A  Color Temperature in Kelvin 5000  Dimensions and Weight  Diameter 0.82 INCH  Length 45.19 Inch  Descriptions  Additional Information ROHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumper Watt; Visible Light Area 325 Degree; Temperature -4 to 11:  Deg F  Commodity Description Led Linear Fluorescent Straight, U-Shape & Circular Lamps  Description *DISCONTINUED* 13W 120-277V 50K T5 LED  Long Description LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPE  45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC  APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOLTACE RATING; 0.82 INCH DIAMETER	Glass Finish	FROSTED
Woltage Rating Wattage  Material, Color, and Finish Base Type Color Rendering Index Book Color Temperature in Kelvin  Diameter Length Diameter Length Additional Information  RoHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumper Watt; Visible Light Area 325 Degree; Temperature -4 to 11: Deg F Commodity Description Long Description Linear Fluorescent Straight, U-Shape & Circular Lamps Additional Information Linear Fluorescent Led Lamp, Linear, Instant Start Type Additional Canada And Us), UL, NSF/ANSI, ETL, DLC APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOLTACE RATING; 0.82 INCH DIAMETER		
Voltage Rating Wattage 120 to 277 Volt AC Wattage 13 Watt  Material, Color, and Finish Base Type Color Rendering Index 80 A Color Temperature in Kelvin 5000  Dimensions and Weight Diameter Length 45.19 Inch  Descriptions Additional Information RoHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumper Watt; Visible Light Area 325 Degree; Temperature -4 to 11: Deg F Commodity Description Led Linear Fluorescent Straight, U-Shape & Circular Lamps Description *DISCONTINUED* 13W 120-277V 50K T5 LED Long Description LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPE 45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOLT AC VOLTAGE RATING; 0.82 INCH DIAMETER	Item	LED Lamp
Material, Color, and FinishBase TypeG5 Miniature 2-PinColor Rendering Index80 AColor Temperature in Kelvin5000Dimensions and WeightDiameter0.82 INCHLength45.19 InchDescriptionsAdditional InformationRoHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumper Watt; Visible Light Area 325 Degree; Temperature -4 to 11: Deg FCommodity DescriptionLed Linear Fluorescent Straight, U-Shape & Circular LampsDescription*DISCONTINUED* 13W 120-277V 50K T5 LEDLong DescriptionLINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPH45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLCAPPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOLTAGE RATING; 0.82 INCH DIAMETER	Voltage Rating	120 to 277 Volt AC
Base Type G5 Miniature 2-Pin Color Rendering Index 80 A Color Temperature in Kelvin 5000  Dimensions and Weight Diameter 0.82 INCH Length 45.19 Inch  Descriptions Additional Information RoHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumper Watt; Visible Light Area 325 Degree; Temperature -4 to 11: Deg F Commodity Description Led Linear Fluorescent Straight, U-Shape & Circular Lamps Description *DISCONTINUED* 13W 120-277V 50K T5 LED Long Description LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPE 45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOLTAC VOLTAGE RATING; 0.82 INCH DIAMETER	Wattage	13 Watt
Color Rendering Index Color Temperature in Kelvin  Dimensions and Weight Diameter Length Descriptions  Additional Information  RoHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumper Watt; Visible Light Area 325 Degree; Temperature -4 to 11: Deg F  Commodity Description Led Linear Fluorescent Straight, U-Shape & Circular Lamps Description Long Description Linear Fluorescent Led Lamp, Linear, Instant Start Type 45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOL: AC VOLTAGE RATING; 0.82 INCH DIAMETER	Material, Color, and Finish	
Color Temperature in Kelvin 5000  Dimensions and Weight Diameter 0.82 INCH Length 45.19 Inch  Descriptions  Additional Information RoHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumper Watt; Visible Light Area 325 Degree; Temperature -4 to 11: Deg F  Commodity Description Led Linear Fluorescent Straight, U-Shape & Circular Lamps Description *DISCONTINUED* 13W 120-277V 50K T5 LED Long Description LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPE 45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOLTAGE RATING; 0.82 INCH DIAMETER	Base Type	G5 Miniature 2-Pin
Dimensions and Weight Diameter Length Descriptions Additional Information RoHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumo per Watt; Visible Light Area 325 Degree; Temperature -4 to 113 Deg F Commodity Description Led Linear Fluorescent Straight, U-Shape & Circular Lamps Description *DISCONTINUED* 13W 120-277V 50K T5 LED Long Description LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPE 45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOLTAC VOLTAGE RATING; 0.82 INCH DIAMETER	Color Rendering Index	80 A
Diameter Length  45.19 Inch  Descriptions  Additional Information  RoHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumo per Watt; Visible Light Area 325 Degree; Temperature -4 to 11: Deg F  Commodity Description  Led Linear Fluorescent Straight, U-Shape & Circular Lamps Description  *DISCONTINUED* 13W 120-277V 50K T5 LED  Long Description  LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPH 45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOLTAC VOLTAGE RATING; 0.82 INCH DIAMETER	Color Temperature in Kelvin	5000
Length 45.19 Inch  Descriptions  Additional Information RoHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumo per Watt; Visible Light Area 325 Degree; Temperature -4 to 11: Deg F  Commodity Description Led Linear Fluorescent Straight, U-Shape & Circular Lamps Description *DISCONTINUED* 13W 120-277V 50K T5 LED Long Description LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPH 45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOLTACE RATING; 0.82 INCH DIAMETER	<b>Dimensions and Weight</b>	
Additional Information  RoHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumo per Watt; Visible Light Area 325 Degree; Temperature -4 to 113 Deg F  Commodity Description  Led Linear Fluorescent Straight, U-Shape & Circular Lamps  Description  *DISCONTINUED* 13W 120-277V 50K T5 LED  Long Description  LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPE 45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOLTAC VOLTAGE RATING; 0.82 INCH DIAMETER	Diameter	0.82 INCH
Additional Information  RoHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumo per Watt; Visible Light Area 325 Degree; Temperature -4 to 113 Deg F  Commodity Description  Description  Led Linear Fluorescent Straight, U-Shape & Circular Lamps  *DISCONTINUED* 13W 120-277V 50K T5 LED  Long Description  LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPE  45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC  APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOLTACE RATING; 0.82 INCH DIAMETER	Length	45.19 Inch
Additional Information  RoHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumo per Watt; Visible Light Area 325 Degree; Temperature -4 to 113 Deg F  Commodity Description  Description  Led Linear Fluorescent Straight, U-Shape & Circular Lamps  *DISCONTINUED* 13W 120-277V 50K T5 LED  Long Description  LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPE  45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC  APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOLTACE RATING; 0.82 INCH DIAMETER	Descriptions	
Description *DISCONTINUED* 13W 120-277V 50K T5 LED  Long Description LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPI  45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC  APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOLT  AC VOLTAGE RATING; 0.82 INCH DIAMETER		RoHS Compliant; Shatter Proof Coated Glass; Efficacy 139 Lumen per Watt; Visible Light Area 325 Degree; Temperature -4 to 113 Deg F
Long Description  LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPE  45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC  APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOLT  AC VOLTAGE RATING; 0.82 INCH DIAMETER	Commodity Description	Led Linear Fluorescent Straight, U-Shape & Circular Lamps
45.19 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL, DLC APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOL AC VOLTAGE RATING; 0.82 INCH DIAMETER	Description	*DISCONTINUED* 13W 120-277V 50K T5 LED
	Long Description	APPROVAL; FOOD EQUIPMENT APPLICATION; 120 TO 277 VOLT
Product rype Linear Fluorescent Led Lamp	Product Type	Linear Fluorescent Led Lamp



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

и	•	IABLIT	· ^ ^ †	COLID	forma	STIAN
•	•	141111	41 1111	~		4116311

Brand	Keystone Technologies	
Manufacturers Part Number	KT-LED13T5HE-48GC-850-D	
Model	800	

#### **Taxonomies, Classifications, and Categories**

Category Description	LED LINEAR STRAIGHT(Fluor replacement), U-SHAPE & CIRCULAR
	LAMPS
Туре	Linear, Instant Start

#### **Packaging**

··· <del>···</del> j····j		
Carton	25	
Weight Per each	0.516	
9		

### Uses, Certifications, and Standards

Application	Food Equipment
Approval	UL (Canada and US), UL, NSF/ANSI, ETL, DLC