



# Elite BR Series

TCP's Elite series LED BR Lamps combine the long life and energy savings of LED technology with the look and feel of a traditional halogen lamp.

## Limitless options for the following applications:

- Recessed Downlights
- Track Lights
- Display Lights
- Outdoor Fixtures that Protect Lamps from the Elements

## Great features and benefits:

- Energy Efficient: 80% more efficient than incandescent
- Smooth, uniform dimming; also available as non-dimming
- Long Life: 25,000 hours
- 85W, 65W, 60W and 50W replacements
- Smooth outer housing
- Excellent color consistency and high color rendering (CRI)
- Available in 2400K, 2700K, 3000K, 4100K and 5000K



BR40



BR30



R20



LED  
we know light.™



325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com

©TCP NOV 2016/WF26353





## ELITE Series

## LED BR40, BR30 and R20 Lamps

**LED** 25,000 Hours average rated life, 120 Volts

### Applications:

Ideal for BR40, BR30, AND R20 flood and spot light applications.

- + Recessed Downlights
- + Track Lights
- + Display Lights
- + Outdoor Fixtures that Protect Lamps from the Elements



### Features

### Benefits

|                                                 |                                                                                                                |
|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Up to 85% less energy than halogen alternatives | Instant energy savings                                                                                         |
| Long life                                       | Minimizes replacement and maintenance costs                                                                    |
| Smooth, clean outside housing                   | Seamlessly blends into lighting applications                                                                   |
| Very low heat generation                        | Perfect for sensitive display lighting such as art galleries                                                   |
| Excellent Color Consistency and CRI             | Enhances colors of focal point while maintaining uniformity throughout lighting installation from lamp to lamp |
| Low weight                                      | Track or down light installations are not strained by excess weight                                            |
| UL approved for damp location                   | Can be used outdoors when protected from elements. Withstands humidity indoors/outdoors                        |
| Shatter resistant                               | Lower the risk of injury and breakage                                                                          |
| Rated for totally enclosed fixtures             | Can be used indoors or outdoors in enclosed fixtures                                                           |



BR40



BR30



R20



Catalog Number

Notes

Type



### Specifications

|                        |            |
|------------------------|------------|
| Input Line Voltage:    | 120 VAC    |
| Input Power            | See Chart  |
| Input Line Frequency   | 50/60HZ    |
| Lamp Life (Rated)      | 25,000 hrs |
| Minimum Starting Temp  | -30°C      |
| Maximum Operating Temp | 40°C       |
| CRI                    | 80         |

### Replacements

|             |       |
|-------------|-------|
| 17W BR40    | = 85W |
| 12W BR40/30 | = 65W |
| 9W BR30     | = 65W |
| 10W R20     | = 60W |
| 8W R20      | = 50W |



**5 YEAR WARRANTY\***

\*Based on 12 hours use per day

TCP®  
325 Campus Dr. | Aurora, Ohio 44202 | P: 1-800-324-1496 | tcp.com

For the most up-to-date specs, please visit [www.tcp.com](http://www.tcp.com)

©TCP NOV 2016/WF26353



## ELITE Series

## LED Dimmable BR40, BR30 and R20 Lamps

Smooth Uniform Dimming

| Lamp Type                                                                           | Item # | Description   | Voltage                          | Wattage | Lumens | LPW  | M.O.L.<br>(inches) | Diameter<br>(inches) | CCT | CRI   | Case<br>Quantity |    |
|-------------------------------------------------------------------------------------|--------|---------------|----------------------------------|---------|--------|------|--------------------|----------------------|-----|-------|------------------|----|
|    | 17W    | LED17BR40D24K | Dimmable 17W Smooth BR40 - 2400K | 120     | 17     | 960  | 56.5               | 6.0                  | 5.0 | 2400K | 80               | 12 |
|                                                                                     |        | LED17BR40D27K | Dimmable 17W Smooth BR40 - 2700K | 120     | 17     | 1200 | 70.6               | 6.0                  | 5.0 | 2700K | 80               | 12 |
|                                                                                     |        | LED17BR40D30K | Dimmable 17W Smooth BR40 - 3000K | 120     | 17     | 1250 | 73.5               | 6.0                  | 5.0 | 3000K | 80               | 12 |
|                                                                                     |        | LED17BR40D41K | Dimmable 17W Smooth BR40 - 4100K | 120     | 17     | 1300 | 76.5               | 6.0                  | 5.0 | 4100K | 80               | 12 |
|                                                                                     |        | LED17BR40D50K | Dimmable 17W Smooth BR40 - 5000K | 120     | 17     | 1350 | 79.4               | 6.0                  | 5.0 | 5000K | 80               | 12 |
|                                                                                     | 12W    | LED12BR40D24K | Dimmable 12W Smooth BR40 - 2400K | 120     | 12     | 680  | 56.7               | 6.0                  | 5.0 | 2400K | 80               | 12 |
|                                                                                     |        | LED12BR40D27K | Dimmable 12W Smooth BR40 - 2700K | 120     | 12     | 840  | 70.0               | 6.0                  | 5.0 | 2700K | 80               | 12 |
|                                                                                     |        | LED12BR40D30K | Dimmable 12W Smooth BR40 - 3000K | 120     | 12     | 850  | 70.8               | 6.0                  | 5.0 | 3000K | 80               | 12 |
|                                                                                     |        | LED12BR40D41K | Dimmable 12W Smooth BR40 - 4100K | 120     | 12     | 875  | 72.9               | 6.0                  | 5.0 | 4100K | 80               | 12 |
|                                                                                     |        | LED12BR40D50K | Dimmable 12W Smooth BR40 - 5000K | 120     | 12     | 925  | 77.1               | 6.0                  | 5.0 | 5000K | 80               | 12 |
|  | 12W    | LED12BR30D24K | Dimmable 12W Smooth BR30 - 2400K | 120     | 12     | 680  | 56.7               | 5.4                  | 3.8 | 2400K | 80               | 12 |
|                                                                                     |        | LED12BR30D27K | Dimmable 12W Smooth BR30 - 2700K | 120     | 12     | 850  | 70.8               | 5.4                  | 3.8 | 2700K | 80               | 12 |
|                                                                                     |        | LED12BR30D30K | Dimmable 12W Smooth BR30 - 3000K | 120     | 12     | 875  | 72.9               | 5.4                  | 3.8 | 3000K | 80               | 12 |
|                                                                                     |        | LED12BR30D41K | Dimmable 12W Smooth BR30 - 4100K | 120     | 12     | 900  | 75.0               | 5.4                  | 3.8 | 4100K | 80               | 12 |
|                                                                                     |        | LED12BR30D50K | Dimmable 12W Smooth BR30 - 5000K | 120     | 12     | 950  | 75.0               | 5.4                  | 3.8 | 5000K | 80               | 12 |
|                                                                                     | 9W     | LED9BR30D24K  | Dimmable 9W Smooth BR30 - 2400K  | 120     | 9      | 575  | 63.9               | 5.4                  | 3.8 | 2400K | 80               | 12 |
|                                                                                     |        | LED9BR30D27K  | Dimmable 9W Smooth BR30 - 2700K  | 120     | 9      | 700  | 77.8               | 5.4                  | 3.8 | 2700K | 80               | 12 |
|                                                                                     |        | LED9BR30D30K  | Dimmable 9W Smooth BR30 - 3000K  | 120     | 9      | 720  | 80.0               | 5.4                  | 3.8 | 3000K | 80               | 12 |
|                                                                                     |        | LED9BR30D41K  | Dimmable 9W Smooth BR30 - 4100K  | 120     | 9      | 740  | 80.2               | 5.4                  | 3.8 | 4100K | 80               | 12 |
|                                                                                     |        | LED9BR30D50K  | Dimmable 9W Smooth BR30 - 5000K  | 120     | 9      | 775  | 86.1               | 5.4                  | 3.8 | 5000K | 80               | 12 |
|  | 10W    | LED10R20D24K  | Dimmable 10W Smooth R20 - 2400K  | 120     | 10     | 520  | 52.0               | 3.5                  | 2.5 | 2400K | 80               | 12 |
|                                                                                     |        | LED10R20D27K  | Dimmable 10W Smooth R20 - 2700K  | 120     | 10     | 660  | 66.0               | 3.5                  | 2.5 | 2700K | 80               | 12 |
|                                                                                     |        | LED10R20D30K  | Dimmable 10W Smooth R20 - 3000K  | 120     | 10     | 700  | 70.0               | 3.5                  | 2.5 | 3000K | 80               | 12 |
|                                                                                     |        | LED10R20D41K  | Dimmable 10W Smooth R20 - 4100K  | 120     | 10     | 725  | 72.5               | 3.5                  | 2.5 | 4100K | 80               | 12 |
|                                                                                     |        | LED10R20D50K  | Dimmable 10W Smooth R20 - 5000K  | 120     | 10     | 750  | 75.0               | 3.5                  | 2.5 | 5000K | 80               | 12 |
|                                                                                     | 8W     | LED8R20D24K   | Dimmable 8W Smooth R20 - 2400K   | 120     | 8      | 400  | 50.0               | 3.5                  | 2.5 | 2400K | 80               | 12 |
|                                                                                     |        | LED8R20D27K   | Dimmable 8W Smooth R20 - 2700K   | 120     | 8      | 575  | 71.9               | 3.5                  | 2.5 | 2700K | 80               | 12 |
|                                                                                     |        | LED8R20D30K   | Dimmable 8W Smooth R20 - 3000K   | 120     | 8      | 600  | 75.0               | 3.5                  | 2.5 | 3000K | 80               | 12 |
|                                                                                     |        | LED8R20D41K   | Dimmable 8W Smooth R20 - 4100K   | 120     | 8      | 625  | 78.1               | 3.5                  | 2.5 | 4100K | 80               | 12 |
|                                                                                     |        | LED8R20D50K   | Dimmable 8W Smooth R20 - 5000K   | 120     | 8      | 650  | 81.3               | 3.5                  | 2.5 | 5000K | 80               | 12 |



5 YEAR WARRANTY\*

\*Based on 12 hours use per day



**5 YEAR**  
WARRANTY\*

\*Based on 12 hours use per day



## ELITE Series

## LED Non-Dimmable BR40, BR30 and R20 Lamps

| Lamp Type                                                                                   | Item #       | Description                          | Voltage | Wattage | Lumens | LPW  | M.O.L.<br>(inches) | Diameter<br>(inches) | CCT   | CRI | Case<br>Quantity |
|---------------------------------------------------------------------------------------------|--------------|--------------------------------------|---------|---------|--------|------|--------------------|----------------------|-------|-----|------------------|
| BR40<br>   | <b>17W</b>   |                                      |         |         |        |      |                    |                      |       |     |                  |
|                                                                                             | LED17BR4024K | Non-Dimmable 17W Smooth BR40 - 2400K | 120     | 17      | 960    | 56.5 | 6.0                | 5.0                  | 2400K | 80  | 12               |
|                                                                                             | LED17BR4027K | Non-Dimmable 17W Smooth BR40 - 2700K | 120     | 17      | 1200   | 70.6 | 6.0                | 5.0                  | 2700K | 80  | 12               |
|                                                                                             | LED17BR4030K | Non-Dimmable 17W Smooth BR40 - 3000K | 120     | 17      | 1250   | 73.5 | 6.0                | 5.0                  | 3000K | 80  | 12               |
|                                                                                             | LED17BR4041K | Non-Dimmable 17W Smooth BR40 - 4100K | 120     | 17      | 1300   | 76.5 | 6.0                | 5.0                  | 4100K | 80  | 12               |
|                                                                                             | LED17BR4050K | Non-Dimmable 17W Smooth BR40 - 5000K | 120     | 17      | 1350   | 79.4 | 6.0                | 5.0                  | 5000K | 80  | 12               |
|                                                                                             | <b>12W</b>   |                                      |         |         |        |      |                    |                      |       |     |                  |
|                                                                                             | LED12BR4024K | Non-Dimmable 12W Smooth BR40 - 2400K | 120     | 12      | 680    | 56.7 | 6.0                | 5.0                  | 2400K | 80  | 12               |
|                                                                                             | LED12BR4027K | Non-Dimmable 12W Smooth BR40 - 2700K | 120     | 12      | 850    | 70.8 | 6.0                | 5.0                  | 2700K | 80  | 12               |
|                                                                                             | LED12BR4030K | Non-Dimmable 12W Smooth BR40 - 3000K | 120     | 12      | 875    | 72.9 | 6.0                | 5.0                  | 3000K | 80  | 12               |
| BR30<br> | <b>12W</b>   |                                      |         |         |        |      |                    |                      |       |     |                  |
|                                                                                             | LED12BR3024K | Non-Dimmable 12W Smooth BR30 - 2400K | 120     | 12      | 680    | 56.7 | 5.4                | 3.8                  | 2400K | 80  | 12               |
|                                                                                             | LED12BR3027K | Non-Dimmable 12W Smooth BR30 - 2700K | 120     | 12      | 850    | 70.8 | 5.4                | 3.8                  | 2700K | 80  | 12               |
|                                                                                             | LED12BR3030K | Non-Dimmable 12W Smooth BR30 - 3000K | 120     | 12      | 875    | 72.9 | 5.4                | 3.8                  | 3000K | 80  | 12               |
|                                                                                             | LED12BR3041K | Non-Dimmable 12W Smooth BR30 - 4100K | 120     | 12      | 900    | 75.0 | 5.4                | 3.8                  | 4100K | 80  | 12               |
|                                                                                             | LED12BR3050K | Non-Dimmable 12W Smooth BR30 - 5000K | 120     | 12      | 950    | 79.2 | 5.4                | 3.8                  | 5000K | 80  | 12               |
|                                                                                             | <b>10W</b>   |                                      |         |         |        |      |                    |                      |       |     |                  |
|                                                                                             | LED10BR3024K | Non-Dimmable 10W Smooth BR30 - 2400K | 120     | 9       | 520    | 52.0 | 5.4                | 3.8                  | 2400K | 80  | 12               |
|                                                                                             | LED10BR3027K | Non-Dimmable 10W Smooth BR30 - 2700K | 120     | 9       | 650    | 72.2 | 5.4                | 3.8                  | 2700K | 80  | 12               |
|                                                                                             | LED10BR3030K | Non-Dimmable 10W Smooth BR30 - 3000K | 120     | 9       | 675    | 75.0 | 5.4                | 3.8                  | 3000K | 80  | 12               |
| R20<br>  | <b>10W</b>   |                                      |         |         |        |      |                    |                      |       |     |                  |
|                                                                                             | LED10R2024K  | Non-Dimmable 10W Smooth R20 - 2400K  | 120     | 10      | 520    | 52.0 | 3.5                | 2.5                  | 2400K | 80  | 12               |
|                                                                                             | LED10R2027K  | Non-Dimmable 10W Smooth R20 - 2700K  | 120     | 10      | 700    | 70.0 | 3.5                | 2.5                  | 2700K | 80  | 12               |
|                                                                                             | LED10R2030K  | Non-Dimmable 10W Smooth R20 - 3000K  | 120     | 10      | 725    | 72.5 | 3.5                | 2.5                  | 3000K | 80  | 12               |
|                                                                                             | LED10R2041K  | Non-Dimmable 10W Smooth R20 - 4100K  | 120     | 10      | 750    | 75.0 | 3.5                | 2.5                  | 4100K | 80  | 12               |
|                                                                                             | <b>8W</b>    |                                      |         |         |        |      |                    |                      |       |     |                  |
|                                                                                             | LED8R2024K   | Non-Dimmable 8W Smooth R20 - 2400K   | 120     | 8       | 400    | 50.0 | 3.5                | 2.5                  | 2400K | 80  | 12               |
|                                                                                             | LED8R2027K   | Non-Dimmable 8W Smooth R20 - 2700K   | 120     | 8       | 500    | 62.5 | 3.5                | 2.5                  | 2700K | 80  | 12               |
|                                                                                             | LED8R2030K   | Non-Dimmable 8W Smooth R20 - 3000K   | 120     | 8       | 515    | 64.4 | 3.5                | 2.5                  | 3000K | 80  | 12               |
|                                                                                             | LED8R2041K   | Non-Dimmable 8W Smooth R20 - 4100K   | 120     | 8       | 530    | 66.3 | 3.5                | 2.5                  | 4100K | 80  | 12               |



5 YEAR  
WARRANTY\*

\*Based on 12 hours use per day

For the most up-to-date specs, please visit [www.tcpi.com](http://www.tcpi.com)



# Elite BR Series

TCP's Elite series LED BR Lamps combine the long life and energy savings of LED technology with the look and feel of a traditional halogen lamp.

## Limitless options for the following applications:

- Recessed Downlights
- Track Lights
- Display Lights
- Outdoor Fixtures that Protect Lamps from the Elements

## Great features and benefits:

- Energy Efficient: 80% more efficient than incandescent
- Smooth, uniform dimming; also available as non-dimming
- Long Life: 25,000 hours
- 85W, 65W, 60W and 50W replacements
- Smooth outer housing
- Excellent color consistency and high color rendering (CRI)
- Available in 2400K, 2700K, 3000K, 4100K and 5000K



BR40



BR30



R20



LED  
we know light.™



325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com

©TCP NOV 2016/WF26353







## ELITE Series

## LED BR40, BR30 and R20 Lamps

**LED** 25,000 Hours average rated life, 120 Volts

### Applications:

Ideal for BR40, BR30, AND R20 flood and spot light applications.

- + Recessed Downlights
- + Track Lights
- + Display Lights
- + Outdoor Fixtures that Protect Lamps from the Elements



### Features

### Benefits

|                                                 |                                                                                                                |
|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Up to 85% less energy than halogen alternatives | Instant energy savings                                                                                         |
| Long life                                       | Minimizes replacement and maintenance costs                                                                    |
| Smooth, clean outside housing                   | Seamlessly blends into lighting applications                                                                   |
| Very low heat generation                        | Perfect for sensitive display lighting such as art galleries                                                   |
| Excellent Color Consistency and CRI             | Enhances colors of focal point while maintaining uniformity throughout lighting installation from lamp to lamp |
| Low weight                                      | Track or down light installations are not strained by excess weight                                            |
| UL approved for damp location                   | Can be used outdoors when protected from elements. Withstands humidity indoors/outdoors                        |
| Shatter resistant                               | Lower the risk of injury and breakage                                                                          |
| Rated for totally enclosed fixtures             | Can be used indoors or outdoors in enclosed fixtures                                                           |



BR40



BR30



R20



Catalog Number

Notes

Type



### Specifications

|                        |            |
|------------------------|------------|
| Input Line Voltage:    | 120 VAC    |
| Input Power            | See Chart  |
| Input Line Frequency   | 50/60HZ    |
| Lamp Life (Rated)      | 25,000 hrs |
| Minimum Starting Temp  | -30°C      |
| Maximum Operating Temp | 40°C       |
| CRI                    | 80         |

### Replacements

|             |       |
|-------------|-------|
| 17W BR40    | = 85W |
| 12W BR40/30 | = 65W |
| 9W BR30     | = 65W |
| 10W R20     | = 60W |
| 8W R20      | = 50W |



5 YEAR WARRANTY\*

\*Based on 12 hours use per day

TCP®  
325 Campus Dr. | Aurora, Ohio 44202 | P: 1-800-324-1496 | tcp.com

For the most up-to-date specs, please visit [www.tcp.com](http://www.tcp.com)

©TCP NOV 2016/WF26353



## ELITE Series

## LED Dimmable BR40, BR30 and R20 Lamps

Smooth Uniform Dimming

| Lamp Type                                                                           | Item # | Description   | Voltage                          | Wattage | Lumens | LPW  | M.O.L.<br>(inches) | Diameter<br>(inches) | CCT | CRI   | Case<br>Quantity |    |
|-------------------------------------------------------------------------------------|--------|---------------|----------------------------------|---------|--------|------|--------------------|----------------------|-----|-------|------------------|----|
|    | 17W    | LED17BR40D24K | Dimmable 17W Smooth BR40 - 2400K | 120     | 17     | 960  | 56.5               | 6.0                  | 5.0 | 2400K | 80               | 12 |
|                                                                                     |        | LED17BR40D27K | Dimmable 17W Smooth BR40 - 2700K | 120     | 17     | 1200 | 70.6               | 6.0                  | 5.0 | 2700K | 80               | 12 |
|                                                                                     |        | LED17BR40D30K | Dimmable 17W Smooth BR40 - 3000K | 120     | 17     | 1250 | 73.5               | 6.0                  | 5.0 | 3000K | 80               | 12 |
|                                                                                     |        | LED17BR40D41K | Dimmable 17W Smooth BR40 - 4100K | 120     | 17     | 1300 | 76.5               | 6.0                  | 5.0 | 4100K | 80               | 12 |
|                                                                                     |        | LED17BR40D50K | Dimmable 17W Smooth BR40 - 5000K | 120     | 17     | 1350 | 79.4               | 6.0                  | 5.0 | 5000K | 80               | 12 |
|                                                                                     | 12W    | LED12BR40D24K | Dimmable 12W Smooth BR40 - 2400K | 120     | 12     | 680  | 56.7               | 6.0                  | 5.0 | 2400K | 80               | 12 |
|                                                                                     |        | LED12BR40D27K | Dimmable 12W Smooth BR40 - 2700K | 120     | 12     | 840  | 70.0               | 6.0                  | 5.0 | 2700K | 80               | 12 |
|                                                                                     |        | LED12BR40D30K | Dimmable 12W Smooth BR40 - 3000K | 120     | 12     | 850  | 70.8               | 6.0                  | 5.0 | 3000K | 80               | 12 |
|                                                                                     |        | LED12BR40D41K | Dimmable 12W Smooth BR40 - 4100K | 120     | 12     | 875  | 72.9               | 6.0                  | 5.0 | 4100K | 80               | 12 |
|                                                                                     |        | LED12BR40D50K | Dimmable 12W Smooth BR40 - 5000K | 120     | 12     | 925  | 77.1               | 6.0                  | 5.0 | 5000K | 80               | 12 |
|  | 12W    | LED12BR30D24K | Dimmable 12W Smooth BR30 - 2400K | 120     | 12     | 680  | 56.7               | 5.4                  | 3.8 | 2400K | 80               | 12 |
|                                                                                     |        | LED12BR30D27K | Dimmable 12W Smooth BR30 - 2700K | 120     | 12     | 850  | 70.8               | 5.4                  | 3.8 | 2700K | 80               | 12 |
|                                                                                     |        | LED12BR30D30K | Dimmable 12W Smooth BR30 - 3000K | 120     | 12     | 875  | 72.9               | 5.4                  | 3.8 | 3000K | 80               | 12 |
|                                                                                     |        | LED12BR30D41K | Dimmable 12W Smooth BR30 - 4100K | 120     | 12     | 900  | 75.0               | 5.4                  | 3.8 | 4100K | 80               | 12 |
|                                                                                     |        | LED12BR30D50K | Dimmable 12W Smooth BR30 - 5000K | 120     | 12     | 950  | 75.0               | 5.4                  | 3.8 | 5000K | 80               | 12 |
|                                                                                     | 9W     | LED9BR30D24K  | Dimmable 9W Smooth BR30 - 2400K  | 120     | 9      | 575  | 63.9               | 5.4                  | 3.8 | 2400K | 80               | 12 |
|                                                                                     |        | LED9BR30D27K  | Dimmable 9W Smooth BR30 - 2700K  | 120     | 9      | 700  | 77.8               | 5.4                  | 3.8 | 2700K | 80               | 12 |
|                                                                                     |        | LED9BR30D30K  | Dimmable 9W Smooth BR30 - 3000K  | 120     | 9      | 720  | 80.0               | 5.4                  | 3.8 | 3000K | 80               | 12 |
|                                                                                     |        | LED9BR30D41K  | Dimmable 9W Smooth BR30 - 4100K  | 120     | 9      | 740  | 80.2               | 5.4                  | 3.8 | 4100K | 80               | 12 |
|                                                                                     |        | LED9BR30D50K  | Dimmable 9W Smooth BR30 - 5000K  | 120     | 9      | 775  | 86.1               | 5.4                  | 3.8 | 5000K | 80               | 12 |
|  | 10W    | LED10R20D24K  | Dimmable 10W Smooth R20 - 2400K  | 120     | 10     | 520  | 52.0               | 3.5                  | 2.5 | 2400K | 80               | 12 |
|                                                                                     |        | LED10R20D27K  | Dimmable 10W Smooth R20 - 2700K  | 120     | 10     | 660  | 66.0               | 3.5                  | 2.5 | 2700K | 80               | 12 |
|                                                                                     |        | LED10R20D30K  | Dimmable 10W Smooth R20 - 3000K  | 120     | 10     | 700  | 70.0               | 3.5                  | 2.5 | 3000K | 80               | 12 |
|                                                                                     |        | LED10R20D41K  | Dimmable 10W Smooth R20 - 4100K  | 120     | 10     | 725  | 72.5               | 3.5                  | 2.5 | 4100K | 80               | 12 |
|                                                                                     |        | LED10R20D50K  | Dimmable 10W Smooth R20 - 5000K  | 120     | 10     | 750  | 75.0               | 3.5                  | 2.5 | 5000K | 80               | 12 |
|                                                                                     | 8W     | LED8R20D24K   | Dimmable 8W Smooth R20 - 2400K   | 120     | 8      | 400  | 50.0               | 3.5                  | 2.5 | 2400K | 80               | 12 |
|                                                                                     |        | LED8R20D27K   | Dimmable 8W Smooth R20 - 2700K   | 120     | 8      | 575  | 71.9               | 3.5                  | 2.5 | 2700K | 80               | 12 |
|                                                                                     |        | LED8R20D30K   | Dimmable 8W Smooth R20 - 3000K   | 120     | 8      | 600  | 75.0               | 3.5                  | 2.5 | 3000K | 80               | 12 |
|                                                                                     |        | LED8R20D41K   | Dimmable 8W Smooth R20 - 4100K   | 120     | 8      | 625  | 78.1               | 3.5                  | 2.5 | 4100K | 80               | 12 |
|                                                                                     |        | LED8R20D50K   | Dimmable 8W Smooth R20 - 5000K   | 120     | 8      | 650  | 81.3               | 3.5                  | 2.5 | 5000K | 80               | 12 |



5 YEAR WARRANTY\*

\*Based on 12 hours use per day



5 YEAR  
WARRANTY\*

\*Based on 12 hours use per day



## ELITE Series

## LED Non-Dimmable BR40, BR30 and R20 Lamps

| Lamp Type                                                                                   | Item #       | Description                          | Voltage | Wattage | Lumens | LPW  | M.O.L.<br>(inches) | Diameter<br>(inches) | CCT   | CRI | Case<br>Quantity |
|---------------------------------------------------------------------------------------------|--------------|--------------------------------------|---------|---------|--------|------|--------------------|----------------------|-------|-----|------------------|
| BR40<br>   | <b>17W</b>   |                                      |         |         |        |      |                    |                      |       |     |                  |
|                                                                                             | LED17BR4024K | Non-Dimmable 17W Smooth BR40 - 2400K | 120     | 17      | 960    | 56.5 | 6.0                | 5.0                  | 2400K | 80  | 12               |
|                                                                                             | LED17BR4027K | Non-Dimmable 17W Smooth BR40 - 2700K | 120     | 17      | 1200   | 70.6 | 6.0                | 5.0                  | 2700K | 80  | 12               |
|                                                                                             | LED17BR4030K | Non-Dimmable 17W Smooth BR40 - 3000K | 120     | 17      | 1250   | 73.5 | 6.0                | 5.0                  | 3000K | 80  | 12               |
|                                                                                             | LED17BR4041K | Non-Dimmable 17W Smooth BR40 - 4100K | 120     | 17      | 1300   | 76.5 | 6.0                | 5.0                  | 4100K | 80  | 12               |
|                                                                                             | LED17BR4050K | Non-Dimmable 17W Smooth BR40 - 5000K | 120     | 17      | 1350   | 79.4 | 6.0                | 5.0                  | 5000K | 80  | 12               |
|                                                                                             | <b>12W</b>   |                                      |         |         |        |      |                    |                      |       |     |                  |
|                                                                                             | LED12BR4024K | Non-Dimmable 12W Smooth BR40 - 2400K | 120     | 12      | 680    | 56.7 | 6.0                | 5.0                  | 2400K | 80  | 12               |
|                                                                                             | LED12BR4027K | Non-Dimmable 12W Smooth BR40 - 2700K | 120     | 12      | 850    | 70.8 | 6.0                | 5.0                  | 2700K | 80  | 12               |
|                                                                                             | LED12BR4030K | Non-Dimmable 12W Smooth BR40 - 3000K | 120     | 12      | 875    | 72.9 | 6.0                | 5.0                  | 3000K | 80  | 12               |
| BR30<br> | <b>12W</b>   |                                      |         |         |        |      |                    |                      |       |     |                  |
|                                                                                             | LED12BR3024K | Non-Dimmable 12W Smooth BR30 - 2400K | 120     | 12      | 680    | 56.7 | 5.4                | 3.8                  | 2400K | 80  | 12               |
|                                                                                             | LED12BR3027K | Non-Dimmable 12W Smooth BR30 - 2700K | 120     | 12      | 850    | 70.8 | 5.4                | 3.8                  | 2700K | 80  | 12               |
|                                                                                             | LED12BR3030K | Non-Dimmable 12W Smooth BR30 - 3000K | 120     | 12      | 875    | 72.9 | 5.4                | 3.8                  | 3000K | 80  | 12               |
|                                                                                             | LED12BR3041K | Non-Dimmable 12W Smooth BR30 - 4100K | 120     | 12      | 900    | 75.0 | 5.4                | 3.8                  | 4100K | 80  | 12               |
|                                                                                             | LED12BR3050K | Non-Dimmable 12W Smooth BR30 - 5000K | 120     | 12      | 950    | 79.2 | 5.4                | 3.8                  | 5000K | 80  | 12               |
|                                                                                             | <b>10W</b>   |                                      |         |         |        |      |                    |                      |       |     |                  |
|                                                                                             | LED10BR3024K | Non-Dimmable 10W Smooth BR30 - 2400K | 120     | 9       | 520    | 52.0 | 5.4                | 3.8                  | 2400K | 80  | 12               |
|                                                                                             | LED10BR3027K | Non-Dimmable 10W Smooth BR30 - 2700K | 120     | 9       | 650    | 72.2 | 5.4                | 3.8                  | 2700K | 80  | 12               |
|                                                                                             | LED10BR3030K | Non-Dimmable 10W Smooth BR30 - 3000K | 120     | 9       | 675    | 75.0 | 5.4                | 3.8                  | 3000K | 80  | 12               |
| R20<br>  | <b>10W</b>   |                                      |         |         |        |      |                    |                      |       |     |                  |
|                                                                                             | LED10R2024K  | Non-Dimmable 10W Smooth R20 - 2400K  | 120     | 10      | 520    | 52.0 | 3.5                | 2.5                  | 2400K | 80  | 12               |
|                                                                                             | LED10R2027K  | Non-Dimmable 10W Smooth R20 - 2700K  | 120     | 10      | 700    | 70.0 | 3.5                | 2.5                  | 2700K | 80  | 12               |
|                                                                                             | LED10R2030K  | Non-Dimmable 10W Smooth R20 - 3000K  | 120     | 10      | 725    | 72.5 | 3.5                | 2.5                  | 3000K | 80  | 12               |
|                                                                                             | LED10R2041K  | Non-Dimmable 10W Smooth R20 - 4100K  | 120     | 10      | 750    | 75.0 | 3.5                | 2.5                  | 4100K | 80  | 12               |
|                                                                                             | <b>8W</b>    |                                      |         |         |        |      |                    |                      |       |     |                  |
|                                                                                             | LED8R2024K   | Non-Dimmable 8W Smooth R20 - 2400K   | 120     | 8       | 400    | 50.0 | 3.5                | 2.5                  | 2400K | 80  | 12               |
|                                                                                             | LED8R2027K   | Non-Dimmable 8W Smooth R20 - 2700K   | 120     | 8       | 500    | 62.5 | 3.5                | 2.5                  | 2700K | 80  | 12               |
|                                                                                             | LED8R2030K   | Non-Dimmable 8W Smooth R20 - 3000K   | 120     | 8       | 515    | 64.4 | 3.5                | 2.5                  | 3000K | 80  | 12               |
|                                                                                             | LED8R2041K   | Non-Dimmable 8W Smooth R20 - 4100K   | 120     | 8       | 530    | 66.3 | 3.5                | 2.5                  | 4100K | 80  | 12               |



5 YEAR  
WARRANTY\*

\*Based on 12 hours use per day

For the most up-to-date specs, please visit [www.tcpi.com](http://www.tcpi.com)