



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



LED14T848GC835S 14W Led T8 48" 35K CTD GLS

Keystone Technologies

Catalog Number	LED14T848GC835S
Manufacturer	Keystone Technologies
Description	Linear Fluorescent Straight Led Lamp, Linear, Instant Start Type; 47.15 Inch; UI (Canada and Us), UI, NSF/Ansi Approval; Food Equipment, Splash Zone, Dry and Damp Location Application; 1 Inch Diameter; 14 Watt Wattage; Led Tube
Weight per unit	0.6500 (lbs/each)
Product Category	20160825093403

Features

Beam Spread Angle	220 Degree
Glass Finish	FROSTED
Intensity	1800 LUMEN
Item	LED Tube
Wattage	14 Watt

Material, Color, and Finish

Base Type	G13 Medium 2-Pin
Color Rendering Index	80 A
Color Temperature in Kelvin	3500

Dimensions and Weight

Diameter	1 INCH
Length	47.15 Inch

Descriptions

Additional Information	RoHS Compliant; Shatter Proof Coated Glass; System Wattage 22.1 Watt; Efficacy 128.6 Lumen per Watt; Light Spread Angle 325 Degree; Temperature -4 to 113 Deg F
Commodity Description	Led Linear Fluorescent Straight, U-Shape & Circular Lamps
Description	14W LED T8 48" 35K CTD GLS
Long Description	LINEAR FLUORESCENT STRAIGHT LED LAMP, LINEAR, INSTANT START TYPE; 47.15 INCH; UL (CANADA AND US), UL, NSF/ANSI APPROVAL; FOOD EQUIPMENT, SPLASH ZONE, DRY AND DAMP LOCATION APPLICATION; 1 INCH DIAMETER; 14 WATT WATTAGE; LED TUBE

Manufacturer Information

Brand	Keystone Technologies
Manufacturers Part Number	KT-LED14T8-48GC-835-S
Model	800



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	LED LINEAR STRAIGHT(Fluor replacement), U-SHAPE & CIRCULAR LAMPS
----------------------	--

Type	Linear, Instant Start
------	-----------------------

Availability

Status	Inactive
--------	----------

Packaging

Carton	1
--------	---

Package	25
---------	----

Weight Per each	0.65
-----------------	------

Uses, Certifications, and Standards

Application	Food Equipment, Splash Zone, Dry and Damp Location
-------------	--

Approval	UL (Canada and US), UL, NSF/ANSI
----------	----------------------------------