



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



LED15T8L48FGDIM8 15W Led T8 50K Glass Type A 2200LM

Sylvania-Ledvance

Catalog Number	LED15T8L48FGDIM8
Manufacturer	Sylvania-Ledvance
Description	4FT Substitube Led T8 Value, Frosted Glass, 15W, 82 Cri, 2200 Lumens, 5000K, 50, 000 HRS Life, Dimmable
Weight per unit	0.4670 (lbs/each)
Product Category	Lighting

Features

accessories	RoHS
amperage rating	TH
ANSI Code	Medium
average life class	RoHS PROP65: WARNING: Cancer and Reproductive Harm. This product contains material that, the State of California has determined, may cause cancer www.p65warnings.ca.gov
Coil Voltage	4.000 4.000
dimensions	4.000 4.000
dimnable	Open Office, Retail
Fixture Type	Medium
Lamp Included	Lighting
Lamp Type	Osram
lumens	LEDVANCE LLC
Phase	24.000 10.000
Response Time	4.000 4.000
Shape	Cooper Fail-Safe
Voltage Rating	cULus

Material, Color, and Finish

Color	Fluorescent industrial lighting fixture
-------	---

Dimensions and Weight

Diameter	RoHS
Size	Auto

Descriptions

Description	15W LED T8 50K GLASS TYPE A 2200LM
extra long description	SYL LED15T8L48FGDIM850SUBG9/41829 L
Long Description	4ft SubstiTUBE LED T8 Value, Frosted Glass, 15W, 82 CRI, 2200 Lumens, 5000K, 50,000 hrs Life, Dimmable
Product Type	LED15T8L48FGDIM850SUBG9 25/CS 1/Sku



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Manufacturer Information

Brand	Ledvance LLC
GTIN	00046135418297
Manufacturers Part Number	LED15T8L48FGDIM850SUBG9/41829
sub brand	24.000 10.000
UPC	046135418297

Taxonomies, Classifications, and Categories

Category Description	LED LINEAR STRAIGHT(Fluor replacement), U-SHAPE & CIRCULAR LAMPS
----------------------	--

Trade Size

aperture size	RoHS
---------------	------

Packaging

Carton	1
Package	25
Weight Per each	0.467

Uses, Certifications, and Standards

Application	Osram
environmental conditions	RoHS