

## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LL300M 3" LL FM5 Conduit Body Crouse-Hinds	
Catalog Number	LL300M
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 5 Conduit Outlet Body, Malleable Iron, LL Shape, 3"
Weight per unit	13.7 (lbs/each)
Product Category	
Features	
dimensions	13.8700 IN X 4.7500 IN X 5.8700 IN
Form	
Material, Color, and Finish	
Finish	Hot Dip Galvanized
	Thor Dip Guivalinzou
Dimensions and Weight  Height	4.75
Height Hub Size	
	13.87
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	F 07
	5.07
<b>Descriptions</b>	3" LL FM5 CONDUIT BODY
Description extra long description	
Features	Form 5 malleable iron conduit bodies, covers and gaskets from
	Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bends in conduit runs, and provide access to conductors for maintenance and future system changes. Form 5 conduit bodies are manufactured in trade sizes 1/2" to 4", and are interchangeable with Appleton Form 35 conduit bodies. They are also available with a h
Long Description	Eaton Crouse-Hinds series Condulet Form 5 conduit outlet body, Malleable iron, LL shape, 3"
Product Type	3 Form 5 LL Cond Body Malleable
Special Features	Weight 1437 Lb per 100

## **Manufacturer Information**

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274756202
Manufacturers Part Number	LL300M
UPC	782274756202



standard

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories	
Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Туре	Conduit outlet body
Packaging	
Carton	1
Weight Per each	13.7
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other

UL 514B, CSA C22.2, CUL