

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LPCC1610 Low Peak CC TD Bussmann Fuses

Catalog Number	LPCC1610
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series LP-CC Fuse, Current-Limiting Time-Delay Fuse, Rejection Style, 1.6 A, Dual, CC, Non-Indicating, Ferrule End X Ferrule End, 12 Sec At 200%, 200 Kaic At 600 V, 20 Kaic At 300 VDC, Melamine Tube, 10, 600 V, 300 VDC
Weight per unit	0.0200 (lbs/each)
Product Category	
Features	
amperage rating	1.6 A
class	
connection	
dimensions	
element	Dual
interrupt rating	200 kAIC at 600 Vac20 kAIC at 300 Vdc
Material	
media	
Response Time	12 S at 200%
Voltage Rating	600 Vac, 300 Vdc
Dimensions and Weight	
Size	13/32 In Diameter X 1-1/2 In Length
Descriptions	
Description	LOW PEAK CC TD
extra long description	
Features	Bussmann's Class CC fuses set the standard in Class CC fuse performance in the industry. Recognized for their superior performance, Bussmann has the right product for your circuit and equipment protection needs. These branch circuit rated, 600v, 200,000a IR fuses offer exceptional protection in the smallest package of any UL class of fuses. Choose from the ultimate protection provided by our Low Peak LP-CC fuses, the time delay of our FNQ-R's for your control transformer and similar control applications or
Long Description	Eaton Bussmann series LP-CC fuse, Current-limiting time-delay fuse, Rejection style, 1.6 A, Dual, CC, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 200 kAIC at 600 V,20 kAIC at 300 Vdc, Melamine tube, 10, 600 V, 300 Vdc
Product Type	Low Peak CC Time Delay
Special Features	Rejection Style



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	COOPER BUSSMANN
GTIN	00051712180481
Manufacturers Part Number	LP-CC-1-6/10
UPC	051712180481
Taxonomies, Classifications, and Ca	tegories
Category Description	MIDGET FUSES
Туре	FUSE
Packaging	
Carton	10
Weight Per each	0.02
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked, RoHS Compliant