



LPCC212 2-1/2A 600V TD Class CC Low Peak Fuse

Bussmann Fuses

Catalog Number	LPCC212
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class CC Fuse, LP-CC, Time-Delay, Dual-Element Current Limiting Fuse, 2.5 A, Rejection Style Fuse, Interrupting Rating Of 20 Ka At 300 VDC and 200 Ka At 600 Vac
Weight per unit	0.1500 (lbs/each)
Product Category	Current Limiting

Features

amperage rating	2.5
connection	Ferrule End X Ferrule End
dimensions	1.5000 IN X 0.4100 IN X 0.4100 IN
element	Dual
Fuse Class	Class CC
interrupt rating	20 kAIC at 300 Vdc 200 kAIC at 600 Vac
Material	Melamine Tube
media	Yes
Response Time	12 S at 200%
Voltage Rating	600 Vac, 300 Vdc

Dimensions and Weight

Size	13/32 In Diameter X 1-1/2 In Length
------	-------------------------------------

Descriptions

Description	2-1/2A 600V TD CLASS CC LOW PEAK FUSE
extra long description	BUSS LP-CC-2-1/2 LOW PEAK CC TIME D
Features	Bussmann's Class CC fuses set the standard in Class CC fuse performance in the industry. Recognized for their superior performance, Bussmann has the right product for your circuit and equipment protection needs. These branch circuit rated, 600v, 200,000a IR fuses offer exceptional protection in the smallest package of any UL class of fuses. Choose from the ultimate protection provided by our Low Peak LP-CC fuses, the time delay of our FNQ-R's for your control transformer and similar control applications or
Long Description	Eaton Bussmann Series Class CC fuse, LP-CC, time-delay, dual-element current limiting fuse, 2.5 A, rejection style fuse, interrupting rating of 20 kA at 300 Vdc and 200 kA at 600 Vac
Product Type	Low Peak CC Time Delay
Special Features	Rejection Style



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1035 S. Graham St.
76401-0000, TX Stephenville
Phone: 254-965-8083
Fax: 254-968-2662

Manufacturer Information

Brand	Eaton Bussmann series
GTIN	00051712180542
Manufacturers Part Number	LP-CC-2-1/2
UPC	051712180542

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSE

Packaging

Carton	1
Package	10
Weight Per each	0.15

Uses, Certifications, and Standards

Application standard	Ind Facilities & Factories - Facility: Safety and Security Systems UL Listed ,CSA Certified,CE Marked,RoHS Compliant
----------------------	---