Eaton LPJ-12SP

Bussmann LOW-PEAK

LPJ-12SP

Catalog Number: LPJ-12SP

Eaton Bussmann series LPJ fuse, 12 A, Dual, Class J, Non-indicating, Ferrule end x ferrule end, Time delay|Current-limiting, 10 sec at 500%, 100 kAIC Vdc|300 kAIC at 600 V, Standard

General specifications



Eaton Bussmann series LPJ fuse

UPC

051712522748

Product Height

0.81 in

Product Weight

0.19 lb

Compliances
CE Marked

RoHS Compliant

Catalog Number

LPJ-12SP

Product Length/Depth

2.25 in

Product Width

0.81 in

Warranty

Not Applicable



Electrical rating

Amperage Rating

12 A

Interrupt rating

300 kAIC at 600 Vac 100 kAIC Vdc

Response time

10 sec at 500%

Voltage rating

600 Vac, 300 Vdc

Physical details

Fuse type

Time delay

Current-limiting

Number of elements

Dual

Packaging type

Standard

General information

Class

Class J

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

Special features

Indicating, High in-rush current motor protection

Resources

Catalogs

LPJ-12SP~LOW-PEAK CLASS J T/D

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - LPJ-12SP

Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia