

ELLIOTT ELECTRIC SUPPLY 3130 S Dodge Boulevard 85713-0000, AZ Tucson Phone: 520-526-1947 Fax: 520-526-1948



LPJ25SP 25A 600V TD Dual Elem Class J Fuse

Bussmann Fuses

Catalog Number	LPJ25SP
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series LPJ Fuse, Bussmann Series Class J Fuse, LPJ, Time-Delay, Dual-Element Current Limiting Fuse, 25 Amp Non-Idicating Fuse, Interrupting Rating Of 300 Ka At 600 Vac and 100 Ka At 300 VDC
Weight per unit	0.1100 (lbs/each)
Product Category	Dual Element
Features	
amperage rating	25 Amp
class	J
connection	
dimensions	2.2500 IN X 0.8100 IN X 0.8100 IN
element	Dual
interrupt rating	300000 Amp (RMS Symmetrical UL), 100000 Amp (DC)
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc
Dimensions and Weight	
Size	0.81 In Diameter X 2.25 In Length
Descriptions	
Description	25A 600V TD DUAL ELEM CLASS J FUSE
extra long description	BUSS LPJ-25SP BUSSMAN FUSE (55
Features Long Description	Bussmann's UL Class J fuse products extend both our Low-Peak family of products with our LPJ_SP and LPJ_SPI dual-element, time-delay fuses as well as our Limitron line offering fast-acting JKS fuses. The LPJ fuses provide industry leading 300,000 amp interrupting rating at 600Vac RMS Sym and 100kA Vdc while delivering a minimum of 10 seconds of 500 percent rated current ride-through performance which is ideal for sizing of high inrush loads. The LPJ products are available with optional permanent replace fu Eaton Bussmann series LPJ fuse, Bussmann Series Class J fuse, LPJ, time-delay, dual-element current limiting fuse, 25 Amp non-idicating fuse, interrupting rating of 300 kA at 600 Vac and
Dec dust Tues	100 kA at 300 Vdc
Product Type	Bussman Fuse (55



ELLIOTT ELECTRIC SUPPLY 3130 S Dodge Boulevard 85713-0000, AZ Tucson Phone: 520-526-1947 Fax: 520-526-1948

Manufacturer Informa

Brand	Eaton	
GTIN	00051712523288	
Manufacturers Part Number	LPJ-25SP	
UPC	051712523288	

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSF

Packaging

onaging		
Carton	10	
Weight Per each	0.11	

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CSA Certified ,UL Listed,RoHS Compliant