

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4000 Mockingbird Ln 79109-3210, TX Amarillo Phone: 806-220-0404 Fax: 806-220-0811



LPNRK30SP 30A 250V TD Dual Elem Class RK1 Low Peak Fuse Bussmann Fuses

Catalog Number	LPNRK30SP
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class RK1 Fuse, LPN-RK, Time-Delay, Dual-Element, Current Limiting Fuse, 30 A, Non-Indicating Fuse, Interrupting Rating Of 300 Ka At 250 Vac and 100 Ka At 125 VDC
Weight per unit	
Product Category	Dual Element
Features	
amperage rating	30
connection	Ferrule End X Ferrule End
dimensions	2.0000 IN X 0.5600 IN X 0.5600 IN
element	Dual
Fuse Class	Class RK1
interrupt rating	300 kAIC at 250 Vac100 kAIC at 125 Vdc
media	Yes
Response Time	8 S at 500%
Voltage Rating	
Dimensions and Weight	
Size	0.56 In Diameter X 2.00 In Length
Descriptions	•
Description	30A 250V TD DUAL ELEM CLASS RK1 LOW PEAK FUSE
extra long description	BUSS LPN-RK-30SP LOW PEAK DUAL ELEM
Features	Bussmann's UL Class RK1 fuse offering includes the industry's most recognized Low-Peak dual-element, current-limiting, time-delay fuses (LPN-RK and LPS-RK) which are also available with optional indication on select ratings (see product data sheet). Complementing the Low-Peak product offering is
Long Description	Bussmann's Limitron family of fast-acting fuses (KTN-R, KTS-R, KWN-R and KWS-R) fuses. Eaton Bussmann Series Class RK1 fuse, LPN-RK, time-delay, dual-element, current limiting fuse, 30 A, non-indicating fuse, interrupting rating of 300 kA at 250 Vac and 100 kA at 125 Vdc
Product Type	Low Peak Dual Element
Special Features	Indicating, High in-rush current motor protection



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4000 Mockingbird Ln 79109-3210, TX Amarillo Phone: 806-220-0404

Fax: 806-220-0811

					ıtior	

Brand	Eaton
GTIN	00051712538367
Manufacturers Part Number	LPN-RK-30SP
UPC	051712538367

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSE

Packaging

onagn ig		
Carton	10	
Weight Per each	0.05	

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked