

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LPSRK400SP 600V RK1 TD Fuse *Bussmann Fuses*

Catalog Number	LPSRK400SP
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series LPS-RK Fuse, Low-Peak Fuse, 400 A, Dual Class RK1, Non-Indicating, Blade End X Blade End, Time Delay, Current-Limiting, 100 Kaic At 300 VDC, 300 Kaic At 600 V, Standard, 1, 600 V, 300 VDC
Weight per unit	
Product Category	
Features	
amperage rating	400 A
class	Class RK1
connection	
dimensions	11.6300 IN X 2.3600 IN X 2.3600 IN
element	Dual
interrupt rating	100 kAIC at 300 Vdc300 kAIC at 600 Vac
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc
Dimensions and Weight	
Size	2.36 In Diameter X 11.63 In Length
Descriptions	
Description	600V RK1 TD FUSE
extra long description	BUSS LPS-RK-400SP LOW-PEAK DUAL ELE
Features	Bussmann's UL Class RK1 fuse offering includes the industry's most recognized Low-Peak dual-element, current-limiting, time-delay fuses (LPN-RK and LPS-RK) which are also available with optional indication on select ratings (see product data sheet). Complementing the Low-Peak product offering is Bussmann's Limitron family of fast-acting fuses (KTN-R, KTS-R, KWN-R and KWS-R) fuses.
Long Description	Eaton Bussmann series LPS-RK fuse, Low-peak fuse, 400 A, Dual, Class RK1, Non-indicating, Blade end x blade end, Time delay, Current-limiting, 100 kAIC at 300 Vdc, 300 kAIC at 600 V, Standard, 1, 600 V, 300 Vdc
Product Type	Low-Peak Dual Element
Special Features	Electrically Isolated End Cap



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

ivianianactarei innonnatioi	V	lanuf	acturer l	Information
-----------------------------	---	-------	-----------	-------------

Brand	Eaton Bussmann series
GTIN	00051712548557
Manufacturers Part Number	LPS-RK-400SP
UPC	051712548557

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSE

Packaging

Carton	1	
(A.17) (A.7)		
Weight Per each	3.549	

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	RoHS Compliant,CE Marked