



## LR27SA 3/4" Alu LR Cond Body

Appleton/Oz Gedney

Catalog Number	LR27SA
Manufacturer	Appleton/Oz Gedney
Description	FM7 Unilets Type LR Conduit Outlet Body, Hub Size: 3/4 In, Form: 7, Length: 5.19 In, Width: 2.44 In, Material: Aluminum, Finish: Epoxy Powder Coat, Connection: Tapered Female Threaded, Standard: UL 514A, UL 514B, UL File Number E2527, CSA
Weight per unit	0.6000 (lbs/each)
Product Category	Alum

### Features

connection	Tapered Female Threaded
Form	7

### Material, Color, and Finish

Finish	Epoxy Powder Coat
--------	-------------------

### Dimensions and Weight

Hub Size	3/4
Length	5.19
Width	2.44

### Descriptions

Description	3/4" ALU LR COND BODY
extra long description	APP LR27SA 3/4 FM7 BODY TYPE LR- AL
Long Description	FM7 UNILETS Type LR Conduit Outlet Body, Hub Size: 3/4 IN, Form: 7, Length: 5.19 IN, Width: 2.44 IN, Material: Aluminum, Finish: Epoxy Powder Coat, Connection: Tapered Female Threaded, Standard: UL 514A, UL 514B, UL File Number E2527, CSA

Product Type	3/4 FM7 Body Type LR- Alum
Special Features	Accurately tapped, tapered threads for tight, rigid joints and excellent ground continuity; Allow connections for branch runs; Completely interchangeable with Crouse-Hinds Form 7 bodies, gaskets and covers; Connect and change direction of conduit runs; Equivalent FM7 and Form 7 units have identical applications and installation dimensions; Fits flush and snug against flat surfaces for more stable installation; Flat back design provides greater cubic content for easier wire pulling and more room for splicing; Hub



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Manufacturer Information

Brand	Appleton
GTIN	00781381600910
Manufacturers Part Number	LR27SA
UPC	781381600910

## Taxonomies, Classifications, and Categories

Category Description	FORM 7, 8, CONDULETS, COVERS, & GASKETS
Type	Type LR Conduit Outlet Body

## Packaging

Carton	5
Package	40
Weight Per each	0.6

## Uses, Certifications, and Standards

Application standard	For Use With Rigid Steel, Rigid Aluminum Conduit And IMC UL 514A, UL 514B, UL File Number E2527, CSA C22.2 No. 18.3, CSA 065183, NEMA FB-1
----------------------	--