



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



LS7.9360A 14.2" Gray SS Cable Tie

Abb Installation Products, Inc

Catalog Number	LS7.9360A
Manufacturer	Abb Installation Products, Inc
Description	Ball-Lock 304 Stainless Steel Cable Tie, Uncoated, For Temperatures Up to 300 Degrees Celsius (572 F) For Indoor and Outdoor Applications, Suitable For High Temperature Environments, UI/En/CSA62275 Type 2S Rated For Ah-1 Plenum, Length Of 360MM (14.2 Inches), Width Of 7.75MM (0.305 Inches), Thickness Of 0.25MM (0.01 Inches), Tensile Strength Rating Of 2002 Newtons (450 Pounds)
Weight per unit	0.0140 (lbs/each)
Product Category	Cable Ties & Wraps

Features

Bundle Diameter	0.38 to 4 in , 9.7 to 102 mm
Material	304 Stainless Steel
Tensile Strength	450 pounds , 2002 newtons

Material, Color, and Finish

Color	Metallic
-------	----------

Dimensions and Weight

Length	14.2 in , 360 mm
Width	0.305 in , 7.75 mm

Descriptions

Description	14.2" GRAY SS CABLE TIE
extra long description	ABB LS-7.9-360A CABLE TIE 302/304 S
Long Description	Ball-Lock 304 Stainless Steel Cable Tie, Uncoated, for Temperatures up to 300 Degrees Celsius (572 F) for Indoor and Outdoor Applications, Suitable for High Temperature Environments, UL/EN/CSA62275 Type 2S Rated for AH-1 Plenum, Length of 360mm (14.2 Inches), Width of 7.75mm (0.305 inches), Thickness of 0.25mm (0.01 Inches), Tensile Strength Rating of 2002 Newtons (450 Pounds)
Product Type	Cable Tie 302/304 SST 450LB 14 Bal

Manufacturer Information

Brand	Ty-Rap
GTIN	00786210242217
Manufacturers Part Number	LS7.9360A
UPC	786210242217



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
Type	Stainless Steel

Availability

minimum qty	50
-------------	----

Packaging

Carton	50
Package	500
Weight Per each	0.014

Uses, Certifications, and Standards

standard	UL E49405
----------	-----------