

Trade Size

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

LT112UL 1-1/2" Ua Sealtite Conduit, Bonded UI 50'

Catalog Number		
Manufacturer	Southwire Company	
Description	TITAN2 Type UI LFMC Is Manufactured With A Spiral Wound Stoff Heavy Gauge Corrosion-Resistant Hot-Dipped Galvanized Steel. For 3/8" Through 1-1/4" Trade Sizes The Core Is Constructed With A Square Locked Steel Strip With An Integra Copperbonding Strip Enclosed Within The Steel Convolutions. 1-1/2" Through 4" Trade Sizes The Core Is Constructed With A Fully Interlocked Steel Strip. A Rugged Flame Retardant Flexible PVC Jacket Is Extruded Over The Steel Core. The Grey Jacket Resists Oils Mild	
Weight per unit		
Product Category	Conduit & Raceways	
Features		
outside diameter	1882	
Dimensions and Weight		
Length	50	
Descriptions		
Description	1-1/2" UA SEALTITE CONDUIT, BONDED UL	
extra long description	SWC 55093205 Titan2 Type UL Liquidt	
Long Description	Titan2 Type UL LFMC is manufactured with a spiral wound strip of heavy gauge corrosion-resistant hot-dipped galvanized stee For 3/8" through 1-1/4" trade sizes the core is constructed with a square locked steel strip with an integral copperbonding strip enclosed within the steel convolutions. For 1-1/2" through 4" trade sizes the core is constructed with a fully interlocked stee strip. A rugged flame retardant flexible PVC jacket is extruded over the steel core. The grey jacket resists oils mild	
Product Type	TITAN2 Type UI Liquidtight Flexible Metal Conduit	
Manufacturer Information		
Brand	Flexible Conduit	
GTIN	00032886042355	
Manufacturers Part Number	55093205	
UPC	032886042355	
Taxonomies, Classifications, and C	Categories	
Category Description	Liquid Tight	
Туре	LTM-UL	
Trade Size		
	4.4.10	

1 1/2



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Availability Status		
Status	Inactive	
Packaging		
Carton	50	
Weight Per foot	1.12	