

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



#### LTB12545 1-1/4" 45D Insltd LT Conn Crouse-Hinds

Catalog Number	LTB12545
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC,
	45° Angle, Insulated, Malleable Iron, 1-1/4"
Weight per unit	0.8700 (lbs/each)
Product Category	Liquid Tight Fittings

#### **Features**

connection	Threaded
dimensions	3.5000 IN X 2.2500 IN X 3.5000 IN
installation type	THREADED

#### Material, Color, and Finish

Color MALLEABLE IRON	
----------------------	--

### **Descriptions**

Description	1-1/4" 45D INSLTD LT CONN
extra long description	MIDWEST LTB12545 1 1/4 LT 45 DEGREE
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, 45° angle, Insulated, Malleable iron, 1-1/4"
Product Type	1 1/4 LT 45 Degree Conn Insulated

#### **Manufacturer Information**

Brand	Eaton
GTIN	00784564461254
Manufacturers Part Number	LTB12545
UPC	784564461254

## Taxonomies, Classifications, and Categories

Category Description	METALLIC FITTINGS
Туре	Liquidtight connector

### **Trade Size**

Trade Size 1 1/4 in	
---------------------	--



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	5
Weight Per each	0.87
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.93