

Product Number: 64040

Order Abbreviation: M150/SS/U/ED28

General Description: 150W METALARC SUPERSAVER energy saving quartz metal halide lamp, high output, position dedicated, E39 base, ED28 bulb, enclosed fixture rated, clear, universal burn, 4000K

Product Information

Abbrev. With Packaging Info.	M150SSUED28 6/CS 1/SKU
ANSI Code	M107/E:M57/E
ANSI Code 2	M107/E
Approx. Lumens (initial - horizontal)	12000
Approx. Lumens (initial - vertical)	13
Approx. Lumens (mean - horizontal)	5
Approx. Lumens (mean - vertical)	5
Arc Length (in)	0.6
Arc Length (mm)	15
Average Rated Life - Horizontal (hr)	7500
Average Rated Life - (hr)	7500
Average Rated Life - Vertical (hr)	10000
Base	E39 Mogul
Bulb	ED28
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	4000
Diameter (in)	3.504
Diameter (mm)	89
Family Brand Name	Metalarc® Super Saver
Fixture Requirement	E
Hot Restrike Time (min)	7 - 12
Lamp Finish	Clear
Light Center Length - LCL (in)	5
Light Center Length - LCL (mm)	127
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	8.31
Maximum Overall Length - MOL (mm)	211
Nominal Voltage (V)	110.00
Nominal Wattage (W)	150.00
Operating Position	Universal
Warm-up Time (min)	2 - 4

Footnotes

- E = Lamps classified as E-type are to be used ONLY in suitably enclosed luminaries. See lamp warning.
- Operates at 150W on a 175W M57 ballast or a M107 ballast.

Product Number: 64040

Order Abbreviation: M150/SS/U/ED28

General Description: 150W METALARC SUPERSAVER energy saving quartz metal halide lamp, high output, position dedicated, E39 base, ED28 bulb, enclosed fixture rated, clear, universal burn, 4000K

Product Information

Abbrev. With Packaging Info.	M150SSUED28 6/CS 1/SKU
ANSI Code	M107/E:M57/E
ANSI Code 2	M107/E
Approx. Lumens (initial - horizontal)	12000
Approx. Lumens (initial - vertical)	13
Approx. Lumens (mean - horizontal)	5
Approx. Lumens (mean - vertical)	5
Arc Length (in)	0.6
Arc Length (mm)	15
Average Rated Life - Horizontal (hr)	7500
Average Rated Life - (hr)	7500
Average Rated Life - Vertical (hr)	10000
Base	E39 Mogul
Bulb	ED28
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	4000
Diameter (in)	3.504
Diameter (mm)	89
Family Brand Name	Metalarc® Super Saver
Fixture Requirement	E
Hot Restrike Time (min)	7 - 12
Lamp Finish	Clear
Light Center Length - LCL (in)	5
Light Center Length - LCL (mm)	127
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	8.31
Maximum Overall Length - MOL (mm)	211
Nominal Voltage (V)	110.00
Nominal Wattage (W)	150.00
Operating Position	Universal
Warm-up Time (min)	2 - 4

Footnotes

- E = Lamps classified as E-type are to be used ONLY in suitably enclosed luminaries. See lamp warning.
- Operates at 150W on a 175W M57 ballast or a M107 ballast.