



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



M2117423 Multi-Purpose Poly Labels + Ribbon, 0.5" X 1"

Brady Worldwide, Inc.

Catalog Number	M2117423
Manufacturer	Brady Worldwide, Inc.
Description	Harsh Environment Multi-Purpose Polyester Labels With Ribbon Pre-Sized For M210 M211 Printers - 0.5" X 1"
Weight per unit	0.2000 (lbs/each)
Product Category	Builders Products

Features

labels per package	Cartridge of 121 Labels
Material	Polyester
Temperature Range	-94 °F - 230 °F

Material, Color, and Finish

Color	Black on White
Finish	Gloss

Dimensions and Weight

Height	0.5
Size	0.5 in H x 1 in W
Thickness	0.003
Width	1

Descriptions

Description	MULTI-PURPOSE POLY LABELS + RIBBON, 0.5" X 1"
extra long description	BRADY M21-17-423 M21 Polyester Label Cartridge
Features	Harsh environment applications require tough materials and Brady's B-423 polyester stands up to the challenge. Designed to handle the rigors of renewable energy applications, these pre-sized labels are ideal for a wide variety of difficult surfaces in an array of environmental conditions.
Long Description	Harsh Environment Multi-Purpose Polyester Labels with Ribbon Pre-Sized for M210 M211 Printers - 0.5" x 1"
Product Type	M21 Polyester Labels 0.5 X 1 BK/WH
Special Features	Aggressive Adhesive;Harsh Environment;Heat Resistant;Permanent Adhesive

Manufacturer Information

Brand	Brady®
GTIN	00888434558447
Manufacturers Part Number	M21-17-423
UPC	888434558447



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	Printers and Labeling
Type	Label

Packaging

Carton	1
Weight Per each	0.2

Uses, Certifications, and Standards

Application	Barcode Labeling;Component and Equipment Labeling;General Identification;Inventory and Inspection Labeling
standard	Halogen Free (DIN VDE 0472 Part 815)