



**Product Number:** 64036

**Order Abbreviation:** M400/U/ED37

**General Description:** 400W METALARC quartz metal halide lamp, E39 base, ED37 bulb, enclosed fixture rated, universal burn, clear, 4000K

#### Product Information

Abbrev. With Packaging Info.	M400UED37 6/CS 1/SKU
ANSI Code 2	M59/S
Approx. Lumens (initial - horizontal)	32000
Approx. Lumens (initial - vertical)	36
Approx. Lumens (mean - horizontal)	21
Approx. Lumens (mean - vertical)	24
Arc Length (in)	1.177
Arc Length (mm)	45
Average Rated Life - Horizontal (hr)	15000
Average Rated Life - (hr)	15000
Average Rated Life - Vertical (hr)	20000
Base	E39 Mogul
Bulb	ED37
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	4000
Diameter (in)	4.606
Diameter (mm)	117
Family Brand Name	Metalarc®
Fixture Requirement	S
Hot Restrike Time (min)	7 - 12
Lamp Finish	Clear
Light Center Length - LCL (in)	5
Light Center Length - LCL (mm)	178
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	11.5
Maximum Overall Length - MOL (mm)	292
Nominal Voltage (V)	135.00
Nominal Wattage (W)	400.00
Operating Position	Universal
Warm-up Time (min)	2 - 4



**Product Number:** 64036

**Order Abbreviation:** M400/U/ED37

**General Description:** 400W METALARC quartz metal halide lamp, E39 base, ED37 bulb, enclosed fixture rated, universal burn, clear, 4000K

#### Product Information

Abbrev. With Packaging Info.	M400UED37 6/CS 1/SKU
ANSI Code 2	M59/S
Approx. Lumens (initial - horizontal)	32000
Approx. Lumens (initial - vertical)	36
Approx. Lumens (mean - horizontal)	21
Approx. Lumens (mean - vertical)	24
Arc Length (in)	1.177
Arc Length (mm)	45
Average Rated Life - Horizontal (hr)	15000
Average Rated Life - (hr)	15000
Average Rated Life - Vertical (hr)	20000
Base	E39 Mogul
Bulb	ED37
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	4000
Diameter (in)	4.606
Diameter (mm)	117
Family Brand Name	Metalarc®
Fixture Requirement	S
Hot Restrike Time (min)	7 - 12
Lamp Finish	Clear
Light Center Length - LCL (in)	5
Light Center Length - LCL (mm)	178
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	11.5
Maximum Overall Length - MOL (mm)	292
Nominal Voltage (V)	135.00
Nominal Wattage (W)	400.00
Operating Position	Universal
Warm-up Time (min)	2 - 4