



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2250 West Broadway Road Suite 102
85202-0000, AZ Mesa
Phone: 623-900-2983
Fax: 623-900-2984



MHUB10 4" Mall CNDT Hub *Crouse-Hinds*

Catalog Number	MHUB10
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Mhub Conduit Hub, Malleable Iron, 4"
Weight per unit	0.0200 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

Features

connection	Male Threaded
dimensions	6.2400 IN X 5.4700 IN X 3.4000 IN
Material	Malleable Iron

Material, Color, and Finish

Finish	Zinc Electroplated
--------	--------------------

Dimensions and Weight

Size	4 in
------	------

Descriptions

Description	4" MALL CNDT HUB
extra long description	MIDWEST MHUB10 4 COND HUB MALLEABLE
Features	The use of rigid/IMC conduit remains the preferred choice in many applications because of the physical protection of conductors and long service life of the installation. Consequently, the need to terminate conduit into a box or enclosure creates the need for a hub. The Crouse-Hinds series commercial hub has been developed to provide a lightweight hub that installs quickly and easily, providing a secure termination.
Long Description	Eaton Crouse-Hinds series MHUB conduit hub, Malleable iron, 4"
Product Type	4 Cond Hub Malleable Iron
Special Features	Weight 2 Lb per 100

Manufacturer Information

Brand	Eaton
GTIN	00784564002945
Manufacturers Part Number	MHUB10
UPC	784564002945

Taxonomies, Classifications, and Categories

Category Description	STEEL EMT FITTINGS
Type	Conduit hub

Packaging

Carton	1
Weight Per each	0.02



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2250 West Broadway Road Suite 102
85202-0000, AZ Mesa
Phone: 623-900-2983
Fax: 623-900-2984

Uses, Certifications, and Standards

Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other
Enclosure standard	NEMA FB-1, Class I Div 2, Class II Div 1 2, Class III Div 1 2 UL 514B, CUL, CSA C22.2